

well #2

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 112621
Permit No.
Basin 92 B

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66171

1 OWNER TERRY PLYS
MAILING ADDRESS 11580 OREGON BLVD
NE NE RENO, NV 89506

ADDRESS AT WELL LOCATION 11580 OREGON BLVD
RENO, NV 89506
Subdivision Name:
County: Washoe

2 LOCATION 1/4 1/4 Sec 15 T 21N N/S R 19 E
PERMIT/WAIVER No. R-659 080-414-13
Issued by Water Resources Parcel No.

Latitude 39.69271°N UTM E
Longitude 119.83270°W N
NAD 27
NAD 83/WGS 84

3 TYPE OF WELL
[X] Domestic
[ ] Municipal/Industrial
[ ] Irrigation
[ ] Monitor
[ ] Test
[ ] Stock

Is this well being plugged because a replacement well was drilled? NO
Is there an existing well log? YES
If yes, what is replacement well NOI?
If yes, what is NDWR well log #? 101176

4 EXISTING WELL CONSTRUCTION
Table with columns: Size O.D. (Inches), Weight/Ft (Pounds), Wall Thickness (inches), From (Feet), To (Feet)
Rows: 6 5/8, 5 9/16, 3

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [X] yes [ ] no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? [ ] yes [X] no
Was the casing pulled? [ ] yes [X] no
Was the casing over drilled? [ ] yes [X] no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Existing Perforations:
Table with columns: Type of perforation, Size of perforation, From, To
Type of perforation: FACTORY SLOT
Size of perforation: 3 X 3/32

WAIVER
Table with columns: Type of perforator used, From, To, Number of perfs per linear foot

5 WATER LEVEL
Static water level 348 feet below land surface
Artesian flow
Water temperature POOR °F Quality POOR P.S.I.

8 WELL PLUGGING MATERIALS
Material Used
From 200 feet to 422 feet BENTONITE [ ] Pumped [X] Poured
From 0 feet to 200 feet CEMENT GROUT [X] Pumped [ ] Poured

6 Additional Notes or Comments
0 TO 200' CEMENT GROUT
200' TO 422' HYDRATED BENTONITE ROUND PELLETS
39.692, 801°N NAD27 D.D.
119.831, 674°W

Neat Cement Fluid Weight 96/4 lbs/gal
Bentonite Grout 1/4 BENTONITE PELLETE % bentonite
Date Started 12/08/2010
Date Completed 12/08/2010

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name CAPITAL CITY WELL DRILLING AND PUMP SERVICE INC.
Address # 20 KIT KAT DRIVE
CARSON CITY, NV 89706
Nevada contractor's license number issued by the State Contractor's Board 0055548
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1905
Signed Michael Black
Date 12/13/2010

MWH P