WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 113759
Permit No.
Basin 203

NOTICE OF INTENT NO. 33748

1. OWNER Brent Atkinson
MAILING ADDRESS 74 W. Sunset Circle Brookside, UT 84782
ADDRESS AT WELL LOCATION 5278 Truman Lane Highland Knolls

2. LOCATION SW ¼ N.W ¼ Sec. 2 T. 3 N/S R. 67 E. Lincoln County
PERMIT NO. Issued by Water Resources
013-030-57 Parcel No.
Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Tan Clay, Sand, Gravel & Boulders		0	50	50
Gray Clay, Sand, Gravel, Boulders		50	60	10
3/8-3/4" Sand & Gravel Red		60	70	10
50% 3/8" Gravel, 50% Sand & Clay		70	80	10
3/8"-3/4" Sand, Gravel	X	80	85	5
50% Red Clay, 50% Sand Gravel Cobbles		85	100	15
Red Clay, Sand, Gravel, Cobbles		100	110	10
80% Clay, 15% Sand, 5% 3/8" Gravel		110	120	10
80% Clay, 5% Gravel, 15% Sand		120	135	15
Gray 30% Gravel 70% Sand	X	135	140	5
Red Mudstone (50%), Sand Gravel		140	170	30
80% Gray Sand, 20% Gravel Cobbles	X	170	175	5
50% Red Mudstone, 40% Sand, 10% Gravel		175	185	10
40% Mudstone, 35% Sand, 25% Gravel		185	200	15

1150723960 UTM E
4177394 UTM N

DCNR/DWR
RECEIVED
APR 22 2011
LAS VEGAS OFFICE

Date started April 14, 2011
Date completed April 18, 2011

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		1 Hour

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 7/8 Inches		0 Feet	200 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	17.02	.250	+ 18"	20
6.625	5.006	.390	20	200

Perforations:
Type perforation Mill
Size perforation 1/8"
From 120 feet to 140 feet
From 160 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 200 feet

9. WATER LEVEL
Static water level 88 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Gardner Brothers Drilling (Contractor)
Address PO Box 965 (Contractor)
Enterprise, UT 84725
Nevada contractor's license number issued by the State Contractor's Board 0068459
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1710
Signed Dale Gardner (By driller performing actual drilling on site or contractor)
Date April 20, 2011

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627