STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115760
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36376

1. OWNER Big daddy's oil Lla
MAILING ADDRESS 3230 Flamingo Rd # 8-352 LV NV lasvegas

ADDRESS AT WELL LOCATION 3885 Chartewston Blvd las Vegas NV

2. LOCATION SW ¼ SW ¼ Sec 31 T 20S N/S R 62 E
PERMIT/WAIVER No. 8-000953 (Issued by Water Resources) 140-31-403-002 Parcel No.

Latitude 36.15915
Longitude 115.09377
UTM E
N
☐ NAD 27 ☑ NAD 83/WGS 84
Subdivision Name:
County: Clark

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other...

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other... has

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Attached Copies				
well MW-4				
083120651				

DCNR/DWR
RECEIVED
JUL 12 2012
LAS VEGAS OFFICE

Date started 14-Jun , 20 12
Date completed 15-Jun , 20 12

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 22 Feet Depth Cased 22 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 Inches	0 Feet	22 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	PVC	sch 40	0	22

Perforations:
Type of perforation slotted screen
Size of perforation 0.02
From 7 feet to 22 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 6
Placement Method: ☐ Pumped ☑ Poured
Gravel Packed: ☐ Yes ☐ No
From 6 feet to 22 feet

Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M P.S.I
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eagle Drilling Services, LLC (Contractor)
Address 7150 Placid St (Contractor)
Las Vegas, NV 89119
Nevada contractor's license number issued by the State Contractor's Board 51266
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2097
Signed (By driller performing actual drilling on site or contractor)
Date 6/19/2012

(Rev. 06/10) USE ADDITIONAL SHEETS IF NECESSARY

36.1591783
-115.0929373
NAD 27

Time	PID Reading (ppmv)	Blow Count (per 6 inches)	Sample Number	Sample Interval	Depth (ft)	Lithology	DESCRIPTION OF SUBSURFACE MATERIALS	Well Construction
							Borehole Location: East side of UST Area (same location as B-3 drilled 1/12/12)	
							Total Depth: 22'	
							Depth to Bedrock:	
							Depth to Water: 12'	
							Groundwater Elevation (MSL):	
						Fill	3" asphalt over gravelly sand-brn	0
						CL	SILTY CLAY- brn	4
					5	CL	SILTY CLAY- discolor black w/sl. hydro. odor	6 7
						CL	SANDY CLAY- w/gravel, lt gray w/sl. hydro. odor	
					10			
					15	ML	CLAYEY SILT- red brn, wet	
						CL	SILTY CLAY- red brn, wet	
					20			22
					25		Bg 22'	

DGNR/DWR
RECEIVED
JUL 12 2012
LAS VEGAS OFFICE

Date Started/Completed: 6/15/12

Drilling Agency/Driller: Eagle Drilling

Equipment Used: Mobile B-90

Drilling Method/Fluid: HSA

Hammer Weight/Drop Distance: n/a

Borehole Diameter: 10"

Completion: 4" monitor well

Logged by: T. Aren

Checked by: Keith Stewart

Comments: 3C.15924 115.09370

STEWART ENVIRONMENTAL, INC.

File No.: 11-517.1

LOG OF BORING NO.: MW-4

Page 1 of 1

Hydro. odor seems old, weathered, Not Fresh gasoline

screen: 4" 7' to 22' .020"
sand: #8 6' to 22'
bentonite: 4' to 6'

concrete: 0 to 4'
Emco Wheaton Well Cover