STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115786
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36816

1. OWNER Town Center 3 LLC
MAILING ADDRESS 901 N. Green Valley Pkwy #200
Henderson, NV 89074-7105

ADDRESS AT WELL LOCATION 4900 E. Sunset Road
Henderson NV. 89118
Subdivision Name: County: Clark

2. LOCATION SW ¼ SW ¼ Sec 32 T 21 N/S R 62 E
PERMIT/WAIVER No. 161-32-412-009
Issued by Water Resources Parcel No.

Latitude N 36° 04' 17.5" UTM E ☐ NAD 27
Longitude W 115° 04' 50.4" N ☒ NAD 83/WGS 84
Client # MW-14

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill A/C over Agg Base		0	2	2
SILTY SAND		2	6	4
Gypsum w/sand/Gr.		6	12	6
CALICHE		12	15	3
SANDY GRAVEL		15	19	4
SAND w/clay		19	20	1
SILTY SAND		20	22	2
CALICHE		22	25	3
SAND w/gravel, clay	wet	25	26	1
CALICHE	wet	26	36	10
SANDY GRAVEL	wet	36	45	9

Date started: 9/20, 20 12
Date completed: 9/20, 20 12

9. WELL CONSTRUCTION
Depth Drilled 45 Feet Depth Cased 45 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	45	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch 40 PVC		ASTM F480	0	45

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 25 feet to 45 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 5 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 23 to 45 ☐ Pumped ☒ Poured
Type: #8 Monterey Sand
Bentonite Chips: ☒ Yes ☐ No 23 to 5 ☐ Pumped ☐ Poured
Type: Hydrated 3/8 Bentonite Hole Plug

7. Water Level
Static water level: 25.6 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

DCNR/DWR RECEIVED
OCT 19 2012
LAS VEGAS OFFICE

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc.
Contractor
Address 4255 W. Post Rd
Contractor
Las Vegas, NV. 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944
Signed Thomas M. Beall
By driller performing actual drilling on-site or contractor
Date 10/17/12

(Rev. 06-06)
USE ADDITIONAL SHEETS IF NECESSARY

36.0715537 - NAD 27
115.0798374

(NSPO 3-08) (O) 627