STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 115787
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36816

1. OWNER Town Center 3 LLC
MAILING ADDRESS 901 N. Green Valley Pkwy #200 Henderson, NV 89074-7105
ADDRESS AT WELL LOCATION 4300 E. Sunset Rd. Henderson NV 89074
Subdivision Name: County: Clark

2. LOCATION SW ¼ SW ¼ Sec 32 T 21 N R 62 E
PERMIT/WAIVER No. 161-32-412-009
Issued by Water Resources Parcel No.
Latitude N36° 04' 17.4"
Longitude W115° 04' 53.1"
UTM E ☐ NAD 27
N ☒ NAD 83/WGS 84
Client # MW-13

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill Dc over Agg. base		0	2	2
Clayey Sand w/gravel		2	5	3
Sandy Silt		5	6	1
SILTY SAND		6	8	2
Sand w/so. gr., silt		8	11	3
CALICHE		11	16	5
SANDY Gravel [redacted]		16	19	3
SANDY SILT		19	20	1
Clayey Sand w/gr.		20	22	2
CALICHE		22	23	1
SANDY CLAY		23	24	1
CALICHE	Wet	24	30	6
Clayey Sand	Wet	30	32	2
CALICHE		32	33	1
CLAYEY SAND	Wet	33	34	1
SANDY CLAY w/gr.		34	36	2
CALICHE		36	37	1
SANDY CLAY		37	40	3

Date started: 9/20, 20 12
Date completed: 9/21, 20 12

7. Water Level
Static water level: 26.8 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

DCNR/DWR
RECEIVED
OCT 19 2012

9. WELL CONSTRUCTION
Depth Drilled 40' Feet Depth Cased 40' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch 40 PVC		F480	0	40

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 20 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 5 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 18 to 40 ☐ Pumped ☒ Poured
Type: #8 Monterey SAND
Bentonite Chips: ☒ Yes ☐ No 18 to 5 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug Hydrated

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc.
Contractor
Address 4255 W. Post Rd.
Contractor
Las Vegas, NV. 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944
Signed Thomas N. Beall
By driller performing actual drilling on-site or contractor
Date 10/17/12

(Rev. 05-08)
USE ADDITIONAL SHEETS IF NECESSARY

LAS VEGAS OFFICE 36.0715259 -NAD 27
-115.0805874

(NSPO 3-08) (O) 627