



Ninyo & Moore

MONITORING WELL LOG

MARYLAND PARKWAY LIFT STATION DECOMMISSIONING
LAS VEGAS, NEVADA

PROJECT NO.
303257002

DATE
1/13

FIGURE
A-3

DEPTH (feet)	SAMPLES		BLOWS/FOOT	MOISTURE (%)	DRY DENSITY (PCF)	PID READING (PPM)	SYMBOL	CLASSIFICATION U.S.C.S.	WELL CONSTRUCTION	DATE DRILLED	BORING NO.	
	Bulk	Driven								12/27/12	MW-2	
										GROUND ELEVATION	SHEET	OF
										METHOD OF DRILLING		
										DRIVE WEIGHT	DROP	
										SAMPLED BY	LOGGED BY	REVIEWED BY
										DESCRIPTION/INTERPRETATION		
20								CL		Reddish tan, sandy CLAY.		
25												
30										Total Depth = 30 feet. Groundwater was measured at a depth of approximately 16 feet in borehole. Boring converted to 2" diameter SCH 40 PVC monitoring well on 12/27/12 promptly after completion of drilling.		
35										<u>Note:</u> Groundwater may rise to a level higher than that measured in borehole due to seasonal variations in precipitation and several other factors as discussed in the report.		
40										<p style="text-align: center;">DCNR/DWR RECEIVED</p> <p style="text-align: center;">JAN 18 2013</p> <p style="text-align: center;">LAS VEGAS OFFICE</p>		



MONITORING WELL LOG		
MARYLAND PARKWAY LIFT STATION DECOMMISSIONING LAS VEGAS, NEVADA		
PROJECT NO.	DATE	FIGURE
303257002	1/13	A-4