STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116229
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36965
WELL NAME (if applicable): PHJMW-50

1. OWNER/CLIENT NAME Nick Walden / Clark County
MAILING ADDRESS 1354 Rossini Circle
Henderson, NV 89052

DETAILED ADDRESS AT WELL LOCATION 5100 Paradise Rd
Las Vegas, NV
Subdivision Name: County: Clark

2. PLS LOCATION SE ¼ NW ¼ 27 Sec 21 (S) 61 E
PERMIT/WAIVER NO. 16227202001
Issued by Water Resources Current Parcel No.

Latitude UTM E ☐ NAD 27
Longitude 36°05'49.99" UTM N 115°808'54.21" ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☑ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Asphalt			0	1	1
light brn gm sand grvl			1	1.5	1
brn prly grtd sand sly grvl			1.5	5.5	4
Caliche			5.5	16	11
brn sndy clay grvl			16	20	4
gry snd trce grvl moist			20	26	6
rdsh brn sly cly grvl moist			26	35	9
rdsh brn sly brn sly cly sn			35	40	5
decreas in moister			40	52	12
brn silty clay dry					

Date started: 29-Oct , 20 12
Date completed: 29-Oct , 20 12

DCNR/DWR
RECEIVED
DEC 06 2012
LAS VEGAS OFFICE

7. WATER QUALITIES
Static water level: 17' Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☑ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
Bailer		35	1.5

9. WELL CONSTRUCTION
Depth Drilled: 52 Feet Depth Cased: 52 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8.25	Inches	0	Feet	52	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	52

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 48 Feet To 52 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☑ Sanitary Seal	40	to 45		
☑ Neat Cement	3'	to 40	☐ Pumped	☐ Poured
☐ Cement Grout		to	☑ Pumped	☐ Poured
☑ Concrete Grout	0.5'	to 3'	☐ Pumped	☑ Poured
☐ Bentonite Chips		to	☐ Pumped	☐ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☑ Gravel Pack [> 0.2 in.]	45'	to 52'	☐ Pumped	☑ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National Exploration Wells & Pumps
Contractor
Address 5566 ArrowHighway, Montclair CA 91763
Contractor
Nevada contractor's license number as issued by the State Contractor's Board 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2111-T1
Signed: Bob
By driller performing actual drilling on site or contractor
Date 11/29/2012

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY

36.097247 - NAD27
- 115.147560