STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116232
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36960
WELL NAME (if applicable): OMW-70C

1. OWNER/CLIENT NAME Clark County / Rose Peline Avis Budget Car Rental
MAILING ADDRESS 6 Sylvan Wy Parsippany NJ 07054

DETAILED ADDRESS AT WELL LOCATION 525' S. of Tropicana 40' W of Curb on Maryland Parkway
Subdivision Name: County Clark

2. PLS LOCATION NE ¼ NE ¼ 26 Sec 21 N(S) 61 E
PERMIT/WAIVER NO. 162-227-599-003
Issued by Water Resources Current Permit No

Latitude 36°05'58.86"N UTM E ☐ NAD 27
Longitude 115°08'12.85"W UTM N ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☑ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Asphalt			0	1	1
Gravely Sand/Base			1	3	2
Calliche			3	13	10
Silty Gravely Sand					
Lhgt brn grvl,silty, trc snd			13	16	3
Cleysilt lght brn			16	22	6
cley silt lght brn moist					
Tan clayey silt slighly mst			22	35	13
lght brn clay			35	45	10

DCNR/DWR
RECEIVED
DEC 06 2012
LAS VEGAS OFFICE

Date started: 29-Oct , 20 12
Date completed: 29-Oct , 20 12

9. WELL CONSTRUCTION
Depth Drilled: 30 Feet Depth Cased: 30 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 5/5	Inches	0	Feet	30	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	30

PERFORATIONS
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 25 Feet To 30 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☑ Sanitary Seal	17' to 22'			
☑ Neat Cement	3' to 17'	☑ Pumped	☐ Poured	
☐ Cement Grout	to	☐ Pumped	☐ Poured	
☑ Concrete Grout	0.5' to 3'	☐ Pumped	☑ Poured	
☐ Bentonite Chips	to	☐ Pumped	☐ Poured	
☐ Bentonite Grout	to	☐ Pumped	☐ Poured	
☐ 15 % ☐ 20 % ☐ Other, explain:				
☑ Gravel Pack [> 0.2 in.]	22' to 30'	☐ Pumped	☑ Poured	
☐ Sand Pack [< 0.2 in.]	to	☐ Pumped	☐ Poured	
☐ Other, explain:	to	☐ Pumped	☐ Poured	

7. WATER QUALITIES
Static water level: 0 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality: ND

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National Exploration Wells & Pumps (Contractor)
Address 5566 ArrowHighway, Montclair CA 91763 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2111-T1
Signed: Bob M (By individual performing actual drilling on site or contractor)
Date: 11/29/2012

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY

36.099711
115.136071 -NAD 27