STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116237
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36963
WELL NAME (If applicable): hjmw-74

CLARK county

1. OWNER/CLIENT NAME Rose Peline Avis Budget Car Rental
MAILING ADDRESS 6 Sylvan Wy Parsippany NJ 07054

DETAILED ADDRESS AT WELL LOCATION 5100 Paradise RD
las Vegas
Subdivision Name: County: Clark

2. PLS LOCATION SE ¼ NW ¼ 27 Sec 21 N(S) 61 E
PERMIT/WAIVER NO. 162-27-202-001
Issued by Water Resources Current Parcel No.

Latitude 36°05.47.27'N UTM E ☐ NAD 27
Longitude 115°08'53.91"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / OM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☒ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Concrete			0	1	1
Gravely Sand/Base			1	5.5	5
Calliche			5.5	22	17
Lhgt brn grvl,silty, trc snd			22	35	13
Cleysilt lght brn			35	45	10

DCNR/DWR
RECEIVED
DEC 06 2012
LAS VEGAS OFFICE

Date started: 3-Nov , 20 12
Date completed 3-Nov , 20 12

9. WELL CONSTRUCTION
Depth Drilled: 45 Feet Depth Cased: 45 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 5/5	Inches	0	Feet	45	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	45

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 40' Feet To 45' Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	32'	to	37'		
☒ Neat Cement	3'	to	32'	☐ Pumped	☐ Poured
☐ Cement Grout		to		☒ Pumped	☐ Poured
☒ Concrete Grout	0.5'	to	3'	☐ Pumped	☒ Poured
☐ Bentonite Chips		to		☐ Pumped	☐ Poured
☐ Bentonite Grout		to		☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:					
☒ Gravel Pack [> 0.2 in.]	37'	to	45'	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 0 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality: ND

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National Exploration Wells & Pumps
Contractor
Address 5566 ArrowHighway, Montclair CA 91763
Contractor
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2111-T1
Signed: Bob
By driller performing actual drilling on site or contractor
Date: 11/29/2012

(Rev. 09-12)

USE ADDITIONAL SHEETS IF NECESSARY

36.096492 - NAD 27
-115.147477