

Name: "Well #9"
(See PPOD map)

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

PARTIAL PLUGGING

OFFICE USE ONLY
Log No. 116372
Permit No. 19185
Basin 087

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67774

1 OWNER Truckee Meadows Water Authority
MAILING ADDRESS 1355 Capital Blvd.
Reno, NV. 89502
ADDRESS AT WELL LOCATION 3010 Airmotive Way
Reno, NV.
Subdivision Name: County: Washoe

2 LOCATION NW ¼ SE ¼ Sec 18 T 19N N/S R 20 E
Latitude 39.51N UTM E NAD 27
Longitude 119.78W N NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled?
If yes, what is replacement well NOI?
Is there an existing well log? yes
If yes, what is NDWR well log #? 6021

4 EXISTING WELL CONSTRUCTION
Depth Drilled 685 Feet Depth Cased 685 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
20		.250	0	322
12		.250	250	685

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:

Existing Perforations:

Type of perforation	Size of perforation	From	To
bar-lug screen	0.045	355	665
		405	445
		480	570
		595	610
		625	665

Additional Perforations:

Type of perforator used:	From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature ° F Quality

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	
685	588	feet	neat cement	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
				<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
				<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
				<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
				<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
				<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
Truckee Meadows Water Authority decided to plug bottom screen section of well from 685' back to 580' with neat cement.
Installed 680' of 2" tremme pipe. Pumped in 3 cubic yards of neat cement to plug off bottom 105' of well. Following day we measured top of cement at 612'. Set tremme pipe to 609' and mixed 18 bags of Portland Type II cement with approx. 90 gallons of water and pumped into well. The following day, we measured top of plug at 588' which is 7' inside blank casing.

Neat Cement Fluid Weight 14.5 lbs/gal
Bentonite Grout % bentonite
Date Started 12/21/2011
Date Completed 12/22/2011

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Carson Pump, LLC Contractor
Address P.O. Box 20159 Contractor
Carson City, NV. 89721
Nevada contractor's license number issued by the State Contractor's Board 39920
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265 & 1482
Signed [Signature]
Date 1/6/2012

RECEIVED
2012 JUL -2 PM 1:23
STATE ENGINEERS OFFICE