

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
 Log No. 116612
 Permit No. 19296
 Basin 153

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69288
 Diamond Valley-HC 62 Box 195
 Eureka, NV
 County: Eureka

1 OWNER Owen Miller / KenKaren Properties
 MAILING ADDRESS HC 62 Box 62195
Eureka, NV 89316

ADDRESS AT WELL LOCATION
 Subdivision Name:
 County: Eureka

2 LOCATION SE 1/4 NE 1/4 Sec 28 T 20N N/S R 53 E
 PERMIT/WAIVER No. 19296
 Issued by Water Resources Parcel No.

Latitude 39.56759 N UTM E NAD 27
 Longitude 115.99840 W N NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? Yes
 If yes, what is replacement well NOI? 69287

Is there an existing well log? Yes
 If yes, what is NDWR well log #? orig. deepening 6522/26764

4 EXISTING WELL CONSTRUCTION
 Depth Drilled 268 Feet Depth Cased 268 Feet

7 WELL PLUGGING PROCEDURE
 Was well cleaned out to total depth? yes no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	27	10 ga	0	225
12	44	.240	100	268

If well was not cleaned out to total depth, please explain why:
 Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	To
Mill: Knife Slot	1/4 : 1/2 Knite Slot	150 feet	268 feet

Additional Perforations:

Type of perforater used:	From	To	Number of perfs per linear foot
Mill Knife	100 feet	0 feet	8

5 WATER LEVEL
 Static water level 238 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature Cool °F Quality Unknown

8 WELL PLUGGING MATERIALS

From	To	Material Used	Pumped	Poured
268 feet	50 feet	3/8 Hole Plug	<input type="checkbox"/>	<input checked="" type="checkbox"/>
50 feet	0 feet	Neat Cement	<input type="checkbox"/>	<input checked="" type="checkbox"/>

6 Additional Notes or Comments
 3/8 Hole plug installed from bottom to 50 ft.
 Neat Cement from 50 ft. to Surface
 FEB 29 2013
 STATE ENGINEERS OFFICE

Neat Cement Fluid Weight 15.6 lbs/gal
 Bentonite Grout _____ % bentonite
 Date Started 1/5/2013
 Date Completed 1/5/2013

9 DRILLER'S CERTIFICATION
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
 Name Parsons Drilling, INC Contractor
 Address P.O. Box 1265 Contractor
Fallon, NV 89407
 Nevada contractor's license number 29064
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 2285
 Division of Water Resources, the on-site driller
 Signed [Signature]
 Date 1/10/2013

(Rev 05-06)
39.567662°N
115.996458°W NAD27

USE ADDITIONAL SHEETS IF NECESSARY