STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 116691
Permit No. 58039T
Basin 052

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70085

1 OWNER Newmont Mining
MAILING ADDRESS 1655 Mountain City highway
Elko Nv 89803

ADDRESS AT WELL LOCATION
Golg Quarry mine 6 miles north of carlin
Subdivision Name: *County:* Eureka

2 LOCATION NW¼ SW ¼ Sec 35 T 34 N/S R 51 E
PERMIT/WAIVER No. 58039-T
Issued by Water Resources *Parcel No.*

Latitude
Longitude
UTM E 564626 N 4515289
☑ NAD 27 ☐ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☑ Municipal/Industrial ☐ Irrigation ☐ Monitor ☐ Test ☐ Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 41653

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 1610 Feet Depth Cased 1596 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
40	160		0	40
24	95		O	1596

Existing Perforations:
Type of perforation Louvered
Size of perforation 0.125

From	716	feet to	1556	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

5 *WATER LEVEL*
Static water level feet below land surface
Artesian flow No G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments

Perforated 12 rows from 1580' to 370'
1/4" gravel & bentonite med hole plug 1582'-1275'
Neat cement 1275'-1227'
1/4" gravel & bentonite med hole plug 1227'-426'
Neat cement 426'-368'
Uncontaminated backfill gravel 368'-0'

Neat cement 1-1/4" dip tube

NAD 27
40.78 7953°N
116.23 4045°W

Plugs well log 41653

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☑ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☑ no
Was the casing pulled? ☐ yes ☑ no
Was the casing over drilled? ☑ yes ☐ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used: Star wheel

From 370	feet to	1580	feet	Number of perfs per linear foot	5x12
From	feet to		feet	Number of perfs per linear foot	
From	feet to		feet	Number of perfs per linear foot	
From	feet to		feet	Number of perfs per linear foot	
From	feet to		feet	Number of perfs per linear foot	
From	feet to		feet	Number of perfs per linear foot	

8 WELL PLUGGING MATERIALS

				Material Used		
From 1582	feet to	1275	feet	1/4grvl&holeplug	☐ Pumped	☑ Poured
From 1275	feet to	1227	feet	Neat Cement	☑ Pumped	☐ Poured
From 1227	feet to	426	feet	1/4grvl&holeplug	☐ Pumped	☑ Poured
From 426	feet to	368	feet	Neat Cement	☑ Pumped	☐ Poured
From 368	feet to	0	feet	Gravel Fill	☐ Pumped	☑ Poured
From	feet to		feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight 16 lbs/gal
Bentonite Grout N/A % bentonite
Date Started April 18 2013
Date Completed May 3 2013

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear
Contractor
Address P.O. Box 2748 Elko NV 89803
Contractor

Nevada contractor's license number issued by the *State Contractor's Board* 0021976
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* ~~2436~~ 2446

Signed [signature]
By driller performing actual drilling on site or contractor
Date May 4 2013

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY