

Time	PID Reading (ppmv)	Blow Count (per 6 inches)	Sample Number	Sample Interval	Depth (ft)	DESCRIPTION OF SUBSURFACE MATERIALS		Well Construction
						Lithology	Borehole Location: by SV-1 Total Depth: 23' Depth to Bedrock: Depth to Water: ~11.5' Groundwater Elevation (MSL):	
7:00					0	Fill	4" asphalt pavement over gravelly sand, brn	
				2	CL	CLAYEY SAND - w/ gravel, brn	2'	
				5	CAL	CALICHE - HARD, TAN	5'	
				7.5			7.5'	
9:00	-	17	RW-3 eq. 5'		10	CL	SANDY CLAY - w/ gravel, gray w/ hydrocarbon odor	
				15	CAL	CALICHE - V. HARD, TAN		
				20	CL	SANDY CLAY - w/ some gravel V. moist to wet gray		
					25		Be 23'	23'

Date Started/Completed: March 5, 2013
 Drilling Agency/Driller Eagle
 Equipment Used: Diedrich D-120
 Drilling Method/Fluid: HSA
 Hammer Weight/Drop Distance: 140 lb
 Borehole Diameter: 10"
 Completion: 4" remediation well.

Logged by: T. Aten
 Checked by: Keith Stewart
 Comments:

STEWART ENVIRONMENTAL, INC.

File No.: 07-515.11

LOG OF BORING NO.: RW-3

Page 1 of 1

4" screen .020" slot 8' to 23'
 4" casing to 1'
 #12 sand 7.5' to 23'
 bent seal 5' to 7.5'
 concrete 2' to 5'

DCNR/DWR/SNBO
 RECEIVED

MAR 27 2013

Lat: 36.11428 N
 Long: 115.16341 W