

Time	PID Reading (ppmv)	Blow Count (per 6 inches)	Sample Number	Sample Interval	Depth (ft)	DESCRIPTION OF SUBSURFACE MATERIALS		Well Construction	
						Lithology	Borehole Location: between SV-5 + SV-6 Total Depth: 23' Depth to Bedrock: Depth to Water: ~11' Groundwater Elevation (MSL):		
9:15	2230	28	RW-4 @10.5'	10 to 11'	0	Fill	4" asphalt pavement over gravelly sand, bn		
					1	SM	SILTY SAND - w/ some gravel, bn		2'
					2	CAL	CALICHE - HARD, TAN		4'
					3				7.5'
					4	CL	Gravelly clay - gray w/ str. hydro. odor		B
					5	CL	SILTY CLAY - gray w/ slight hydro odor		
				6	CAL	CALICHE - HARD, TAN			
				15					
				20	CL	SANDY CLAY - w/ gravel, gray wet			
				25	Be 23'		23'		

Date Started/Completed: March 6, 2013
 Drilling Agency/Driller: Eagle
 Equipment Used: Diedrich D120
 Drilling Method/Fluid: HSA
 Hammer Weight/Drop Distance: 140 lb
 Borehole Diameter: 10"
 Completion: 4" remediation well

Logged by: T. Aten
 Checked by: Keith Stewart
 Comments:
STEWART ENVIRONMENTAL, INC.
 File No.: 07-515.11
LOG OF BORING NO.: RW-4
 Page 1 of 1

4" screen 1020 slot 8' to 23'
 4" casing 1' to 8'
 #12 sand 7.5' to 23'
 bent. seal 4' to 7.5'
 concrete 2' to 4'

Lat: 36.11422 N
 Long: 115.16343 W

OCNR/DWR/SNBO RECEIVED

MAR 27 2013