

Time	PID Reading (ppmv)	Blow Count (per 6 inches)	Sample Number	Sample Interval	Depth (ft)	DESCRIPTION OF SUBSURFACE MATERIALS		Well Construction
						Lithology	Borehole Location: <i>East driveway</i> Total Depth: <i>20.5'</i> Depth to Bedrock: Depth to Water: <i>~10'</i> Groundwater Elevation (MSL):	
7:15	-	7	MW-6 29.5'	9'-10'	0-3'	Fill	3" asphalt pavement over gravelly sand, brn	
					3'-4.5'	SM	SILTY SAND - brn	
					4.5'-5'	CL	SILTY CLAY - brn	
					5-10'	ML	SANDY SILT - brn v. moist to wet DCNR/DWR/SNBO RECEIVED APR 10 2013	
					10-16'	CL	SILTY CLAY - w/so sand brn, v. moist to wet	
					16-20.5'		Be 20.5'	

Date Started/Completed: <i>March 26 2013</i>	Logged by: <i>T. Aten</i>
Drilling Agency/Driller: <i>Eagle</i>	Checked by: <i>Keith Stewart</i>
Equipment Used: <i>Mobile B90</i>	Comments:
Drilling Method/Fluid: <i>HSA</i>	STEWART ENVIRONMENTAL, INC.
Hammer Weight/Drop Distance: <i>140 lb</i>	File No.: <i>13-504.1</i>
Borehole Diameter: <i>10"</i>	LOG OF BORING NO.: MW-6
Completion: <i>4" monitor well</i>	Page <i>1</i> of <i>1</i>

4" screen .020" slot 5' - 20'
 #12 sand 4.5' - 20.5'
 bentonite seal 3' - 4.5'
 concrete 0' - 3'
 Emco Wherton cover
 Well surged & bailed of ~15gals after sanding
 LAT: 36.12095° N
 Long: 115.07406° W