

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 117297  
Permit No.  
Basin 067

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69203  
1600 National Guard Wy  
Reno, NV  
County: WASHOE

1 OWNER AVIS BUDGET CAR RENTAL  
MAILING ADDRESS 6 SYLVAN  
MRS SPANN, NV 89504

ADDRESS AT WELL LOCATION  
Subdivision Name:  
County: WASHOE

2 LOCATION SE 1/4 NW 1/4 Sec 19 T 19N N/S/R 20 E  
PERMIT/WAIVER No.

Latitude 14854141.67 UTM E 260845.70 NAD 27  
Longitude 2286639.34 N 43.75721.38 NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  
 Municipal/Industrial  
 Irrigation  
 Monitor  
 Test  
 Stock

Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NO?  
Is there an existing well log?  
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 20.5 Feet  
Depth Cased 20 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/FT (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	.72	.154	.5	20
5 and 40	PVC			

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:

Existing Perforations:  
Type of perforation Machine cut  
Size of perforation .070  
From 10 feet to 20 feet

Additional Perforations:  
Type of perforator used:  
From feet to feet Number of perms per linear foot

5 WATER LEVEL  
Static water level 8 feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

8 WELL PLUGGING MATERIALS  
Material Used  
From 0 feet to .5 feet concrete  Pumped  Poured  
From .5 feet to 20 feet Neat cement  Pumped  Poured

6 Additional Notes or Comments  
Placed drill rod inside 2" PVC casing, over drilled casing with HSA, pulled casing used HSA to trimmie grout (Neat cement)

Neat Cement Fluid Weight lbs/gal  
Bentonite Grout % bentonite  
Date Started 5/29/13  
Date Completed 5/29/13

Plugs unknown well log  
14027  
39.494748 N  
119.781250 W  
2013 JUL 30 PM 2:30  
STATE ENGINEERS BUREAU

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Greg Drilling Contractor  
Address 950 Howe Rd. Contractor  
Martinez CA 94553  
Nevada contractor's license number issued by the State Contractor's Board C 23-0038113  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 22322 M  
Signed [Signature]  
Date 6/16/13