

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 117390  
Permit No. \_\_\_\_\_  
Basin 212

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37617

1. OWNER JAMES H. & TERI WEBB ADDRESS AT WELL LOCATION NDNE  
MAILING ADDRESS 3168 ANZURELO  
PAIM SPRINGS CALIF. 92264 Subdivision Name: \_\_\_\_\_ County: \_\_\_\_\_  
2. LOCATION SE 1/4 NW 1/4 Sec 18 T 19 N/S R 59 E Latitude N 36° 18' 01.0" UTM E  NAD 27  
PERMIT/WAIVER No. 126-18-201-003 Longitude W 115° 25' 003" N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  New Well  Replace  Recondition  
 Deepen  Other  
4. PROPOSED USE  Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  Air  
5. WELL TYPE  Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Sand + Boulder</u>		<u>0</u>	<u>145</u>	
<u>SHALE + GRAVEL</u>		<u>145</u>	<u>175</u>	
<u>HARD ROCK</u>		<u>175</u>	<u>180</u>	
<u>LIME STONE</u>		<u>180</u>	<u>235</u>	
<u>Shale yellow ish</u>		<u>235</u>	<u>280</u>	
<u>LIME STONE</u>		<u>280</u>	<u>535</u>	
<u>BLACK ROCK</u>	<u>X</u>	<u>535</u>	<u>595</u>	<u>120</u>
<u>SHALE yellowish</u>		<u>595</u>	<u>610</u>	
<u>GRAVEL + SHALE</u>	<u>X</u>	<u>610</u>	<u>695</u>	

9. WELL CONSTRUCTION

Depth Drilled	Feet	Depth Cased	Feet
<u>13 1/2</u>		<u>0</u>	
<u>17 1/4</u>		<u>10</u>	
<u>47 8</u>		<u>695</u>	

HOLE DIAMETER (BIT SIZE)

Inches	From	Feet	To	Feet
<u>13 1/2</u>	<u>0</u>	<u>10</u>	<u>10</u>	
<u>17 1/4</u>	<u>10</u>	<u>50</u>	<u>50</u>	
<u>47 8</u>	<u>50</u>	<u>695</u>	<u>695</u>	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8 5/8</u>	<u>16.7</u>	<u>.188</u>	<u>+2</u>	<u>50</u>
<u>6 1/2</u>	<u>480 PVE</u>		<u>+1</u>	<u>695</u>

Perforations:

Type of perforation FACTORY  
Size of perforation .032 Slotted type  
From 635 feet to 695 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement to \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout 0 to 50  Pumped  Poured  
 Concrete Grout to \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 ≥30% Bentonite Grout to \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Type: \_\_\_\_\_  
Bentonite Chips:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Type: \_\_\_\_\_

Date started: 5-17-13, 20  
Date completed: 6-09-13, 20

7. Water Level  
Static water level: 49.5 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: 60.0 °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

DCNR/DWR/SNBO RECEIVED

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name VERNON H. DIMICK Contractor  
Address 13040 Horse Dr. LV. NV. 89166 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 10062  
Nevada driller's license number issued by the Division of Water Resources the on-site driller 552  
Signed V.H. Dimick  
By driller performing actual drilling on-site or contractor  
Date 7-5-13