

ORIGINAL

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 117744
Permit No. 55112
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68294

1 OWNER WINNEMUCCA FARMS
MAILING ADDRESS ONE POTATO RD.
Winnemucca, NV 89445
ADDRESS AT WELL LOCATION WELL 12A
Subdivision Name: County: Humboldt

2 LOCATION NE 1/4 NE 1/4 Sec 31 T 39N N/S R 39 E
PERMIT/WAIVER No. 55112
Latitude 41° 13.145 N UTM E
Longitude 117° 37.229 W N
NAD 27
NAD 83/WGS 84

3 TYPE OF WELL
Domestic
Municipal/Industrial
Irrigation
Monitor
Test
Stock
Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NOI? 68293
Is there an existing well log? YES
If yes, what is NDWR well log #? 36295

4 EXISTING WELL CONSTRUCTION
Depth Drilled 535' Feet
Depth Cased 525' Feet

Table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 16", 250', .250", 0', 525'.

Existing Perforations:
Type of perforation: WIRE WRAP SCREEN
Size of perforation: N/A
From 200' feet to 220' feet
From 250' feet to 260' feet
From 275' feet to 315' feet
From 330' feet to 340' feet
From 360' feet to 370' feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [X] yes [] no
If well was not cleaned out to total depth, please explain why:

Additional Perforations:
Type of perforator used: HOLT AIR PERFORATOR
From 50' feet to 200' feet Number of perfs per linear foot 6 Rows
From 220' feet to 250' feet Number of perfs per linear foot 6 Rows
From 260' feet to 275' feet Number of perfs per linear foot 6 Rows
From 315' feet to 330' feet Number of perfs per linear foot 6 Rows
From 340' feet to 360' feet Number of perfs per linear foot 6 Rows
From 370' feet to 390' feet Number of perfs per linear foot 6 Rows

5 WATER LEVEL
Static water level 64' feet below land surface
Artesian flow NO G.P.M. 0 P.S.I.
Water temperature COOL °F Quality

8 WELL PLUGGING MATERIALS

Table with columns: From, feet to, Material Used. Rows include NEAT CEMENT and BENTONITE GROUT.

6 Additional Notes or Comments
ADDITIONAL EXISTING PERFORATIONS
390' - 400'
435' - 475'
ADDITIONAL PERFORATIONS MADE
400' - 435'
475' - 525'

Neat Cement Fluid Weight 15 LBS lbs/gal
Bentonite Grout 20% % bentonite
Date Started 5/1/2012
Date Completed 5/2/2012

RECEIVED
2012 MAY 31 AM 10:34
STATE ENGINEERS OFFICE

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources - West, Inc. Contractor
Address 4975 W. Winnemucca Blvd. Contractor
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 56797
Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 2437
Signed Michelle Strother
By driller performing actual drilling on site or contractor
Date 5/24/2012

NAD27 41.21983°N, 117.619523°W