

MW-4

FACILITY ID:

4-00340

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 118029  
Permit No.  
Basin 087

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69197

1 OWNER Shell Oil Products ADDRESS AT WELL LOCATION 3155 Rictake Ln  
MAILING ADDRESS 20945 S. Wilmington Ave Reno, NV  
Carson, CA 90815  
Subdivision Name: County: Washoe

2 LOCATION SE 1/4 SE 1/4 Sec 24 T 19 S R 19 E Latitude 39.493191° N UTM E NAD 27  
PERMIT/WAIVER No. Parcel No. 020-24-36 Longitude 119.788487° W N NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? NO  
Is there an existing well log? Yes  
If yes, what is replacement well NOI? If yes, what is NDWR well log #? 88665

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 30 Feet Depth Cased 30 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		5/16 .40	0	30

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used:  
From feet to feet Number of perfs per linear foot

Existing Perforations:  
Type of perforation manufactured  
Size of perforation  
From feet to feet  
From feet to feet  
From feet to feet  
From feet to feet  
From feet to feet

Type of perforator used:  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot  
From feet to feet Number of perfs per linear foot

5 WATER LEVEL  
Static water level feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

8 WELL PLUGGING MATERIALS  
Material Used  
From 30 feet to 0 feet neat cement  Pumped  Poured  
From feet to feet  Pumped  Poured

6 Additional Notes or Comments  
Tremic grout in neat cement, then  
applied 25 p.s.i. for 5 minutes.  
Poured in 20 gallons.

Neat Cement Fluid Weight lbs/gal  
Bentonite Grout % bentonite  
Date Started 11-8-12  
Date Completed 11-8-12

RECEIVED  
2012 DEC -7 PM 11:03  
STATE ENGINEERS OFFICE

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Gregg Drilling & Testing Contractor  
Address 950 Howe Rd Martinez, CA 94553 Contractor  
Nevada contractor's license number issued by the State Contractor's Board C23-0038113  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2328  
Signed [Signature] By either performing actual drilling on site or contractor  
Date 11-26-12

USE ADDITIONAL SHEETS IF NECESSARY

39.493191° N  
119.788487° W  
NAD27