STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 118247
Permit No.
Basin No. 021

NOTICE OF INTENT NO. 63228 ~~632228~~
WELL NAME *(if applicable)*:

1. OWNER/CLIENT NAME Robert & Crystal Smalley
MAILING ADDRESS 10320 Spur Street
Winnemucca, NV 89445

DETAILED ADDRESS AT WELL LOCATION 10320 Spur Street
Winnemucca NV. 89445
Subdivision Name: Rawhide Estate *County:* Humboldt

2. PLS LOCATION SW ¼ NE ¼ 31 Sec 35 N/S 39 E
PERMIT/WAIVER NO. 010-622-08
Issued by Water Resources *Current Parcel No.*

Latitude N 40'86.6886 UTM E ☐ NAD 27
Longitude W 117' 74.3019 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
clay and gravel			0	80	80
clay brown			80	100	20
clay and gravel			100	320	220

RECEIVED 2013 OCT -7 AM 11:31 STATE ENGINEERS OFFICE

NAD27
40.8660882°N
117.7420560°W

Date started: 25-Sep, 20 13
Date completed: 30-Sep, 20 13

7. WATER QUALITIES
Static water level: 150 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool ° Fahrenheit
Water Quality: good

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
40		3 hr

9. WELL CONSTRUCTION
Depth Drilled: 320 Feet Depth Cased: 320 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11	Inches	0	Feet	320	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+2	320

PERFORATIONS:
Type of perforation: Mill slot
Size of perforation: 0.09
From 260 Feet To 320 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☐ Sanitary Seal		to		
☐ Neat Cement		to	☐ Pumped	☐ Poured
☒ Cement Grout	0	to 100	☒ Pumped	Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☐ Bentonite Chips		to	☐ Pumped	☐ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☐ Gravel Pack [> 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Sand Pack [< 0.2 in.]	100	to 320	☐ Pumped	☒ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Stonehouse Drilling
Contractor
Address 7801 Lakeside Dr. Reno NV. 89511
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 0069994
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 1713

Signed: [signature] office
By driller performing actual drilling on site or contractor
Date: 10/4/13

(Rev. 08-12)

USE ADDITIONAL SHEETS IF NECESSARY