

118272

CTMRD PROGRAM MONITORING WELL STRATIGRAPHIC LOG

Drilling Specifications:

Drilling Contractor: Cascade

Drilling Method: hand dug 0-5'

Rig: 50316 S-11'

Driller: Ken Phillips

Boring Diam.: 6 in TD: 11 ft

Development Method: ---

Date Start: 10/11/13 End: 10/21/13

Well Specifications:

Location Description: W. side of F. Wells 100' S. of Arroyo

Coordinates: _____ ft N _____ ft E

Elevation: _____ ft Survey Method: _____

Reference Pt. Description: _____

Well TD: 10 ft bgs Well Diameter: 2 in

Screen Interval: 5-10 ft bgs

First Water: _____ ft bgs

Static Water at completion: _____ ft bgs



WELL ID: VP-21

Project: Vassar East Plumb PSA

Page 1 of 1

LOGGED BY: B. Kearney

Note: Description section to be used to complement and provide additional information to supplement column descriptors to the left, identify any samples collected, and describe any particulars associated with drilling behavior.

Depth	Engineering Properties				1 st Description				2 nd Effects		Depositional Properties				Graphics									
	Density/Consistency	Moisture	Plasticity	Cohesiveness	Transmissivity	Color	Boulder %	Cobble %	Gravel %	Sand %	Silt %	Clay %	USCS Classification	Weathering/Oxidization	Grading	Angularity	Matrix/Clast-Supported	Clast Lithology	Sedimentary Structure	Depositional Environment	Stratigraphic Contact	PID/Samples (ppm)	Lithology	
0																								
5																								
10																								
15																								
20																								
25																								
30																								

6" asphalt, 12" road base, 2" conduit 1 1/2" b/s abandoned
 brn. silty sand w/ gravel (pebbles), sand matrix
 brn. silty gravel w/ sand & cobbles (4"+)
 brn. silty gravel w/ sand, pebbles & cobbles (4"+)

RECEIVED
 2013 OCT 18 11:11 AM
 STATE ENGINEERS OFFICE