

Log 4-118409

CTMRD PROGRAM MONITORING WELL STRATIGRAPHIC LOG

Drilling Specifications:

Well Specifications:

Drilling Contractor: CASCADE

Drilling Method: HAND AUGER/DIG

Rig: _____

Driller: _____

Boring Diam.: 1/2 in TD: 5 ft

Development Method: _____

Date Start: 8/27/13 End: 8/27/13

Location Description: E/S/In SURSHINE BRAN PROSPECT & ZONE

Coordinates: _____ ft N _____ ft E

Elevation: _____ ft Survey Method: _____

Reference Pt. Description: _____

Well TD: 5 ft bgs Well Diameter: 2 in

Screen Interval: 4-5 ft bgs

First Water: _____ ft bgs

Static Water at completion: _____ ft bgs

Depth	Engineering Properties				13 Description						22 Effects		Depositional Properties				Graphics							
	Density/Consistency	Molsture	Plasticity	Cohesiveness	Transmissivity	Color	Boulder %	Cobble %	Gravel %	Sand %	Silt %	Clay %	USCS Classification	Weathering/Oxidization	Grading	Angularity	Matrix/Clast-Supported	Clast Lithology	Sedimentary Structure	Depositional Environment	Stratigraphic Contact	PID/Samples	Lithology	
0																								
1	MD	M	Z	N	M-U	S _{3/3}		15	50	20	-	SM		R ₆	AB	M	B-20	M	F	G		0.0	S _{3/3}	
2	MD	M	Z	N	H	S _{3/3}		5	70	25		SM		R ₆	R	M	B-10	M	F	G		0.0	S _{3/3}	
3	MD	M	Z	N	H	S _{3/3}		5	60	20		SM		R ₆	R	M	B-50	M	F	G		0.0	S _{3/3}	

Note: Description section to be used to complement and provide additional information to supplement column descriptors to the left, identify any samples collected, and describe any particulars associated with drilling behavior.



WELL ID: ASKO-MK24

Project: 135534

Page 1 of 1

LOGGED BY: W. OWENS

Description

0-1" ASBESTOS
 0.5-2" VY DTK GRAY SILTY SAND w/ GRAD & COBBLES, F-C SAND, F-C GRAVEL TO 3", COBBLES UP TO 4-5"
 2-3 DTK RED GR SILTY SAND w/ TRACE GRAN.
 F-C SAND w/ TRACE F-gravel to 1/2"
 3-5 DTK RED GR SILTY SAND w/ COBB & GRAV.
 F-C SAND, COBB TO 4", BOULD - 1"

RECEIVED
 2013 OCT -2 AM 10:38
 STATE ENGINEERS OFFICE