STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 1158564
Permit No.
Basin No. 071

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63229
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME Justin Berryhill
MAILING ADDRESS PO Box 2155
Winnemucca, Nevada 89446

DETAILED ADDRESS AT WELL LOCATION 10680 Spur St.
Winnemucca NV. 89445
Subdivision Name: Rawhide Estates *County:* Humboldt

2. PLS LOCATION NW ¼ SE ¼ 31 Sec 35 N/S 38 E
PERMIT/WAIVER NO. 10-625-06
Issued by Water Resources *Current Parcel No.*

Latitude N 40'51.717 UTM E
Longitude W 117' 44.604 UTM N
[x] NAD 27
NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Deepen: Orig WL#
[ ] Replacement: Original well log #
[ ] Recondition: Original well log #

4. PROPOSED USE
[x] Domestic [ ] Irrigation [ ] Monitor
[ ] Mining / Dewater [ ] Com / Ind [ ] Stock
[ ] Test / Other [ ] Mun / QM [ ] Rec

5. WELL TYPE
[ ] Auger [ ] Rotary [ ] RVC
[ ] Air [x] Mud [ ] Sonic
[ ] Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thick-ness
clay and gravel			0	100	100
clay and gravel with cobb			100	340	240

RECEIVED 2014 JAN -6 AM 11:30 STATE ENGINEERS OFFICE

NAD27
40.861950°N
117.743400°W

Date started: Dec. 30, 20 13
Date completed: 31-Dec, 20 13

9. WELL CONSTRUCTION
Depth Drilled: 340 Feet Depth Cased: 340 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11	Inches	0	Feet	340	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+3	340

PERFORATIONS:
Type of perforation: Mill slot
Size of perforation: 0.09
From 277 Feet To 340 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

[ ] Sanitary Seal		to			
[ ] Neat Cement		to		[ ] Pumped	[ ] Poured
[x] Cement Grout	0	to	100	[x] Pumped	Poured
[ ] Concrete Grout		to		[ ] Pumped	[ ] Poured
[ ] Bentonite Chips		to		[ ] Pumped	[ ] Poured
[ ] Bentonite Grout		to		[ ] Pumped	[ ] Poured
[ ] 15 % [ ] 20 % [ ] Other, explain:					
[ ] Gravel Pack [> 0.2 in.]		to		[ ] Pumped	[ ] Poured
[ ] Sand Pack [< 0.2 in.]	100	to	340	[ ] Pumped	[x] Poured
[ ] Other, explain:		to		[ ] Pumped	[ ] Poured

7. WATER QUALITIES
Static water level: 150 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool ° Fahrenheit
Water Quality: good

8. WELL TEST DATA
Test Method: [ ] Bailer [ ] Pump [x] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
40		3 hr

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Stonehouse Drilling (Contractor)
Address 7801 Lakeside Dr. Reno NV. 89511 (Contractor)

Nevada contractor's license number as issued by the *State Contractor's Board:* 0069994
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on site driller):* 1713
Signed: [signature] office
By driller performing actual drilling on site or contractor
Date: 1/1/2014

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY