STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 119074
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37077
WELL NAME (If applicable): OMW74-72

1. OWNER/CLIENT NAME Ms RosePelino,AvisBudget Car Rent
MAILING ADDRESS 6 Sylvan Way
Parsippany, NJ, 07054

DETAILED ADDRESS AT WELL LOCATION
Wilbur Street & Lulu Ave, Las Vegas
Subdivision Name: County: Clark

2. PLS LOCATION NW ¼ NE ¼ 27 Sec 21S N/S 61 E
PERMIT/WAIVER NO. Issued by Water Resources Current Parcel No.

Latitude 36°5' 55"N UTM E ☒ NAD 27
Longitude 115° 8' 27" W UTM N ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☒ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Asphalt			0		
Type II Base				7	7
silty sand gravel			7	9	2
sandy silt hard pack			9	12	3
Caliche			12	16	4
gravely lean clay sand			16	20	4
caliche gravel			20	25	5
lean clay gravel			25	31	6
Caliche			31	32	1
clayey gravel sand			32	34	2
well graded sand silt grav			34	41	7
hard clay			41	44	3
well graded sand silt grav			44	45	1
well graded sand			45	51	6
silty gravel sand			51	56	5
well graded sand			56	61	5
hard pack silty sand			61	64	3
silty sand gravel			64	66	2
harder pack silty sand gra			66	75	9

DCNR/DWR/SNDO
RECEIVED
JAN 2 8 2014

Date started: 2-Nov , 20 13
Date completed: 13-Nov , 20 13

9. WELL CONSTRUCTION
Depth Drilled: 75 Feet Depth Cased: 72 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 5/8	Inches	0	Feet	75	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	- .50	72

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02
From 67 Feet To 72 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

Sanitary Seal	56	to	64		
☒ Neat Cement	-1	to	2	☒ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	72	to	75	☒ Pumped	☐ Poured
☒ Bentonite Grout	2	to	56	☒ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:					
☐ Gravel Pack [> 0.2 in.]		to		☐ Pumped	☐ Poured
☒ Sand Pack [< 0.2 in.]	64	to	72	☐ Pumped	☒ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 69 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP (Contractor)
Address 5566 Arrow Highway, Montclair, CA 91763 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 00735355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2057
Signed: (By driller performing actual drilling on site or contractor)
Date: 12/23/13

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY

36.09861
-115.14083