STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 119706
Permit No.
Basin No. 085

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62095
WELL NAME *(if applicable)*:

1. OWNER/CLIENT NAME Don Newman
MAILING ADDRESS 2225 Piedras Drive
Sparks, Nevada 89411

DETAILED ADDRESS AT WELL LOCATION 2225 Piedras Drive
Sparks, Nevada 89411
Subdivision Name. *County:* Washoe

2. PLS LOCATION SE ¼ SE ¼ 31 Sec 21N N/S 21E E
PERMIT/WAIVER NO. *Issued by Water Resources* 076-390-21 *Current Parcel No.*

Latitude 39.64134 UTM E ☐ NAD 27
Longitude 119.66488 UTM N x NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well x Deepen: Orig WL# 92433
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
x Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
x Air ☐ Mud ☐ Sonic
Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Hard Rock (Black)			396	443
Volcanic Rock			443	480
Hard Rock With Fractures			480	645
Total depth 645				
depend well log 92433				
Nad 27 39.641429° N 119.663861° W				

Date started: 3-Mar , 20 14
Date completed: 3/7/2014 , 20 14

7. WATER QUALITIES
Static water level: 320 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cool ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
10	350	.5
15	375	.5
20	425	.5
25	550	.5
30	600	1.0

9. INSTRUCTION
Depth Drilled: 645 Feet Depth Cased: 645 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6-1/8 Inches		396 Feet	645 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5-9/16	10.7	.188	380	645

ANNULAR MATERIALS
Sanitary Seal [x] Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ Bentonite Chips to ☐ Pumped ☐ Poured
☐ Gravel Pack [> 0.2 in.] to ☐ Pumped ☐ Poured
☐ Sand Pack [< 0.2 in.] to ☐ Pumped ☐ Poured
x Other, explain: In Place to ☐ Pumped ☐ Poured

PERFORATIONS:
Type of perforation: Factory sawed
Size of perforation: 3/32 x 3

From 380 Feet	To 400 Feet		
From 445 Feet	To 485 Feet		
From 565 Feet	To 585 Feet		
From 625 Feet	To 645 Feet		
From Feet	To Feet		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name A.S.A.P. Pump & Well Service,LLC. *Contractor*
Address P.O. Box 60130 Reno,Nv 89506 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board:* 35387C
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2121
Signed: Larry Webb *By driller performing actual drilling on site or contractor*
Date: 3/11/2014

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.