STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 119741
Permit No.
Basin 033A

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70762

1. OWNER Villalobos Farms
MAILING ADDRESS PO Box 171
Orovada NV 89425

ADDRESS AT WELL LOCATION 1500 Homestead Rd.
Orovada NV
Subdivision Name: County: Humboldt

2. LOCATION NE ¼ NW ¼ Sec. 23 T 42 N S R 37 E
PERMIT/WAIVER No. 003-491-51
Issued by Water Resources Parcel No.

Latitude N 41° 28.893
Longitude W 117° 49.208
UTM E N
■ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☐ Replace ☐ Recondition
■ Deepen ☐ Other

4. PROPOSED USE
■ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ■ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Existing Well	NO	0	108	108
10" Casing	yes	108	120	12
Cemented gravel	yes	120	300	180
clay sand	[illegible]	300		
Nad 27				
41.482550° N				
117.820133° W				
deepens with nearby well log				

Date started: 2-21, 20 14
Date completed: 2-28, 20 14

7. Water Level
Static water level: 108 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality: clear

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ■ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35	NA	6

9. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 7/8	Inches	120 Feet	300 Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"	Steel	.188	0	20
6 5/8	PVC	Sched 40	20	300

Perforations:
Type of perforation Slot
Size of perforation .020
From 260 feet to 300 feet
From feet to feet
From 200 feet to 220 feet
From feet to feet
From feet to feet

Annular Seal: ■ Yes ☐ No
■ Neat Cement 0 to 20 ☐ Pumped ■ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ■ Yes ☐ No 50 to 300 ☐ Pumped ■ Poured
Type: 3/8" Pea
Bentonite Chips: ■ Yes ☐ No 20 to 50 ☐ Pumped ■ Poured
Type: 3/8" chip

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Allied Drilling Inc. (Contractor)
Address 5140 Jungo Rd. (Contractor)
Winnemucca NV. 89445
Nevada contractor's license number issued by the State Contractor's Board 26728
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1563
Signed [illegible] (By driller performing actual drilling on-site or contractor)
Date 3-14-14

USE ADDITIONAL SHEETS IF NECESSARY

(Rev 05-08)

(NSPO 3-08) (O) 627