STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 120236
Permit No.
Basin 070
Previous log 115392

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70768

1. OWNER Oscar Ragan / James McAlevey
MAILING ADDRESS P.O. Box 2141
Winnemucca NV.

ADDRESS AT WELL LOCATION 17605 Rowdy Rd.
Winnemucca NV.
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ NW ¼ Sec 29 T 36 N/S R 36 E
PERMIT/WAIVER No. 3636-29-100-006
Issued by Water Resources Parcel No.

Latitude N 40° 58.187
Longitude W 117° 57.417
UTM E N
■ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ■ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
■ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ■ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand Clay	NO	0	10	10
Fine gravel clay sand	NO	10	80	70
Clay, sand	NO	80	120	40
Sand, clay fine gravel	yes	120	200	80

Nad 27
40.969783° N
117.956450° W
replaces well log 115392

Date started: 5-10, 20 14
Date completed: 5-15, 20 14

9. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 3/4" Inches		0 Feet	200 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4 5/8	Steel	.188	0	10
4 5/8	PVC	Sched 40	10	200

Perforations:
Type of perforation Slot
Size of perforation .025
From 120 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ■ Yes ☐ No
■ Neat Cement 0 to 20 ☐ Pumped ■ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ■ Yes ☐ No 50 to 200 ☐ Pumped ■ Poured
Type: 3/8" Pea
Bentonite Chips: ■ Yes ☐ No 20 to 50 ☐ Pumped ■ Poured
Type: 3/8" chip

7. Water Level
Static water level: 116 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality: clear

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ■ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
10	NA	6

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Allied Drilling Inc. (Contractor)
Address 5140 Jungo Rd. (Contractor)
Winnemucca NV.
Nevada contractor's license number issued by the State Contractor's Board 76778
Nevada driller's license number issued by the Division of Water Resources, the on site driller 1563
Signed (By driller performing actual drilling on-site or contractor)
Date 5-15-14

(Rev. 06-05)
USE ADDITIONAL SHEETS IF NECESSARY

(NSPO 3-08) (O) 627