STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 20698
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38121
WELL NAME (If applicable): DW-5

1. OWNER/CLIENT NAME: Clark County Flood Control
MAILING ADDRESS: 500 S. Grand Central PKWY
Las Vegas, NV 89101

DETAILED ADDRESS AT WELL LOCATION: 300' SW of Arroyo Grande BLVD
Subdivision Name: County: Clark

2. PLS LOCATION: NE ¼ SW ¼ 9 Sec 22S N/S 62 E
PERMIT/WAIVER NO. NW 1348 (Issued by Water Resources) 178-09-396-005 (Current Parcel No.)

Latitude 36 02'46.95"N UTM E ☐ NAD 27
Longitude 115 03'24.79"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☒ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Silty Sandy Clay			0	12	12
Gravel			12	15	3

DCNR/DWR/SNBC
RECEIVED
AUG 29 2014

Date started: 11-Aug, 20 14
Date completed: 11-Aug, 20 14

7. WATER QUALITIES
Static water level: 13 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled: 15 Feet Depth Cased: 15 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
18	Inches	0	Feet	15	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.05
From 5 Feet To 15 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☐ Sanitary Seal		to		
☐ Neat Cement		to	☐ Pumped	☐ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	1	to 3	☐ Pumped	☒ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☒ Gravel Pack [> 0.2 in.]	3	to 15	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name: Cascade Drilling L.P. (Contractor)
Address: 4590 Copper Sage St., Las Vegas, NV 89115 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: C23-0073966
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2234-T1
Signed: (By driller performing actual drilling on site or contractor)
Date: 8-26-14

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY

36.0463999
-115.0560583
NAD 27