

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 120836  
Permit No. \_\_\_\_\_  
Basin 212

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36839

1. OWNER Kady Corp ADDRESS AT WELL LOCATION 1929 N. Las Vegas Blvd  
MAILING ADDRESS 19516 Pathway St Suite B N. Las Vegas, NV 89036  
Santee, CA 92071 Subdivision Name: \_\_\_\_\_ County: Clark

2. LOCATION NW 1/4 SW 1/4 Sec 23 T 20 N R 61 E Latitude N36°11'43.43" UTM E \_\_\_\_\_  NAD 27  
PERMIT/WAIVER No. 139-23-310-047 Longitude W115°07'46.84" N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_ Client Well MW-4

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  Monitor  
 Municipal/Industrial  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>FULL SANDY GRAVEL</u>		<u>0</u>	<u>4</u>	<u>4</u>
<u>CLAYEY SAND</u>		<u>4 1/2</u>	<u>4 1/2</u>	<u>1/2</u>
<u>CLAYEY SAND</u>		<u>4 1/2</u>	<u>7</u>	<u>2 1/2</u>
<u>SANDY CLAY</u>		<u>7 1/2</u>	<u>17</u>	<u>9 1/2</u>
<u>CLAYEY SAND</u>	<u>yes</u>	<u>17</u>	<u>24</u>	<u>3</u>
<u>SANDY CLAY</u>		<u>14</u>	<u>17</u>	<u>3</u>
<u>CLAYEY SAND</u>	<u>yes</u>	<u>17</u>	<u>25</u>	<u>8</u>

9. WELL CONSTRUCTION  
Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet
<u>8</u>	<u>0</u>	<u>25</u>	<u>25</u>

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2" sch. 40 PVC</u>		<u>ASTM 480</u>	<u>0</u>	<u>25</u>

Perforations:

Type of perforation Factory Slots  
Size of perforation 10 1/2 x 20

From 10 feet to 15 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement to \_\_\_\_\_  Pumped  Poured  
 Cement Grout to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout 0 to 2  Pumped  Poured  
 ≥30% Bentonite Grout to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 8 to 25  Pumped  Poured  
Type: 3/8 Material Silica Sand  
Bentonite Chips:  Yes  No 2 to \_\_\_\_\_  Pumped  Poured  
Type: 3/8 Hydrated Bentonite Chips

Date started: 4/28, 20 14  
Date completed: 4/29, 20 14

7. Water Level  
Static water level: 11 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
	<u>N.A.</u>		

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Elite Drilling Inc Contractor  
Address 4255 W. Post Rd Contractor  
Las Vegas, NV 89118  
Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board 054931  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944

Signed Thomas A. Beall  
By driller performing actual drilling on-site or contractor  
Date 5/8/14