

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 121530  
Permit No. \_\_\_\_\_  
Basin 057

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 71321

1 OWNER Church of Jesus Christ of Latter Day Saints ADDRESS AT WELL LOCATION Antelope Valley  
MAILING ADDRESS 3001 N Fifth Street Battle Mountain, NV 89820  
Elko, NV 89801 Subdivision Name: \_\_\_\_\_ County: Lander

2 LOCATION SE 1/4 SW 1/4 Sec 12 T 24N N/S R 40 E Latitude 39.9620 UTM E  NAD 27  
PERMIT/WAIVER No. R-815 Longitude -117.4252 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? yes  
If yes, what is replacement well NOI? 71320  
Is there an existing well log? yes  
If yes, what is NDWR well log #? 88862

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 290 Feet Depth Cased 290 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	0	11
6	3.3	.255	11	29

Existing Perforations:  
Type of perforation saw cut  
Size of perforation 1/8  
From 190 feet to 290 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

5 WATER LEVEL  
Static water level 221 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

6 Additional Notes or Comments  
Pumped 20% bentonite grout from 290' to 20'  
Pumped neat cement from 20' to surface

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: mill knife  
From 150 feet to 190 feet Number of perfs per linear foot 4  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_

8 WELL PLUGGING MATERIALS  
Material Used  
From 0 feet to 20 feet neat cement  Pumped  Poured  
From 20 feet to 290 feet 20% bent. Grout  Pumped  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured

Neat Cement Fluid Weight 15.6 lbs/gal  
Bentonite Grout 20 % bentonite  
Date Started 12/8/2014  
Date Completed 12/9/2014

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Parsons Drilling, Inc. Contractor  
Address P.O. Box 1265 Contractor  
Fallon, NV 89407  
Nevada contractor's license number issued by the State Contractor's Board 29064  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2501  
Signed [Signature] By driller performing actual drilling on site or contractor  
Date 12/10/2014

RECEIVED  
 2014 DEC 17 AM 10:21  
 STATE ENGINEERS OFFICE

NAD 27  
39.962083° N  
117.424259° W