STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122145
Permit No.
Basin No. 071

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72339
WELL NAME (if applicable):

1. OWNER/CLIENT NAME Donovan and Lisa Walker
MAILING ADDRESS 4695 Aurora Ave
Winnemucca NV

DETAILED ADDRESS AT WELL LOCATION 9795 Sabin Dr
Winnemucca NV
Subdivision Name: Tycana County: Humboldt

2. PLS LOCATION SE ¼ SE ¼ 30 Sec 35 N/S 38 E
PERMIT/WAIVER NO. 353830400027
Issued by Water Resources Current Parcel No.

Latitude N40*52'33.214" UTM E ☐ NAD 27
Longitude W117*44'24.047" UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sand		No	0	7
Course gravel cobbles sand		No	7	145
Cemented gravel cobbles clay		No	145	270
Cemented gravel cobbles clay		Yes	270	400

Nad 27
40.875989°N
117.731051°W

Date started: 28-Mar, 20 15
Date completed: 04/07/15, 20 15

7. WATER QUALITIES
Static water level: 270 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 60 ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
30	N/A	8

9. CONSTRUCTION
Depth Drilled: 400 Feet Depth Cased: 400 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8"	Inches	0	Feet	400	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"	steel	.188	0	20
6 5/8"	pvc	Sched 40	20	400

ANNULAR MATERIALS

Sanitary Seal X ☐ Yes ☐ No X

☒ Neat Cement	0	to	20	☐ Pumped	☒ X Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	20	to	50	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	50	to	400	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: slot
Size of perforation: 0.2

From	Feet	To	Feet
340		400	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.

Name Allied Drilling Inc.
Contractor
Address 5140 Jungo Rd Winnemucca NV
Contractor

Nevada contractor's license number as issued by the State Contractor's Board: 76778
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 1563

Signed: [signature]
By driller performing actual drilling on site or contractor
Date: 4-22-15

RECEIVED
2015 APR 27 PM 12:0
STATE ENGINEERS OFFICE

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.