STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124752
Permit No.
Basin No 049

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72768
WELL NAME (If applicable)

1. OWNER/CLIENT NAME: Tyrel Goddard
MAILING ADDRESS: 536 Morse Lane #16
Elko, NV 89801

DETAILED ADDRESS AT WELL LOCATION: 5714 Yosemite Ave.
Subdivision Name: MV Ranchos County: Elko

2. PLS LOCATION: SE ¼ NE ¼ 31 Sec 34 N/S 55 E
PERMIT/WAIVER NO. (Issued by Water Resources): 064 005 001 (Current Parcel No.)

Latitude 40' 47.52 N UTM E ☐ NAD 27
Longitude 115' 48.860 W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Top Soil			0	2
Sand and Gravel			2	12
Silt Stone			12	100
Silt Stone and gravel Mix		115	100	145

NAD 27
40.792079
115.813431

Date started: 03-05, 20 16
Date completed: 03-05, 20 16

9. INSTRUCTION
Depth Drilled: 145 Feet Depth Cased: 145 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	145	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+2	25
6 5/8	pvc	SDR 17	25	145

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

		to			
☒ Neat Cement			☐ Pumped	☒ Poured	
☐ Cement Grout	0	25	☐ Pumped	☐ Poured	
☐ Concrete Grout			☐ Pumped	☐ Poured	
☒ Bentonite Chips	25	105	☐ Pumped	☒ Poured	
☒ Gravel Pack [> 0.2 in.]	105	145	☐ Pumped	☒ Poured	
☐ Sand Pack [< 0.2 in]			☐ Pumped	☐ Poured	
☐ Other, explain:			☐ Pumped	☐ Poured	

PERFORATIONS
Type of perforation: Mill Slot
Size of perforation: .100

From	Feet	To	Feet
125		145	

7. WATER QUALITIES
Static water level: 55 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
28		2

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge
Name: Fertig Drilling Co. (Contractor)
Address: P.O. Box 525 Elko, NV 89803 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0311904
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 1689
Signed: (Driller performing actual drilling on site or contractor)
Date: 3-9-2016

(Rev 12-13) **USE ADDITIONAL SHEETS IF NECESSARY** pg. of pg.