STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124956
Permit No.
Basin No. 054

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72731
WELL NAME (if applicable):

1. OWNER/CLIENT NAME Julie Leloup
MAILING ADDRESS HC 66 Unit 1 Box 8
Beowawe, NV 89821

DETAILED ADDRESS AT WELL LOCATION Lynn Ranch
Subdivision Name: Lynn Ranch County: Eureka

2. PLS LOCATION NE ¼ NE ¼ 1 Sec 30 N/S 49 E
PERMIT/WAIVER NO. 005-260-65
Issued by Water Resources Current Parcel No.

Latitude 40*30.462 UTM E ☐ NAD 27
Longitude 116*23-987 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
top soil			0	2	2
sand & gravel			2	14	12
hard rock			14	40	26
siltstone & small gravel		420	40	460	420
ryolight hard		540	460	560	100

Date started: 4-Apr , 20 15
Date completed: 13-Apr , 20 15

9. WELL CONSTRUCTION
Depth Drilled: 560 Feet Depth Cased: 560 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	560	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+2	20
6 5/8	PVC	SRD17	20	560

PERFORATIONS:
Type of perforation: mill slot
Size of perforation: 0.035
From 440 Feet To 460 Feet
From 540 Feet To 560 Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	5	to 55		
☒ Neat Cement	5	to 25	☐ Pumped	☒ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	25	to 55	☐ Pumped	☒ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☒ Gravel Pack [> 0.2 in.]	55	to 560	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 440 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: c ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
12		4
	NAD 27	
	40.507783	
	116.398869	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Alternative Drilling Co LLC
Contractor
Address P.O. Box 281166, Lamoille, NV 89828
Contractor
Nevada contractor's license number as issued by the State Contractor's Board: 73955
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 1689
Signed: *By driller performing actual drilling on site or contractor
Date: 4-30-15

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY