STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 125036
Permit No.
Basin No. 087

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38551
WELL NAME *(if applicable)*: well#1

1. OWNER/CLIENT NAME GAK Properties Inc
MAILING ADDRESS 548 Broad Hollow Rd
Melville NY 11747

DETAILED ADDRESS AT WELL LOCATION 4660 Aircenter Cir
Reno NV
Subdivision Name. *County* Washoe

2. PLS LOCATION NE ¼ NW ¼ 29 Sec 19N N/S 20 E
PERMIT/WAIVER NO. DW -121 *Issued by Water Resources* 021-451-13 *Current Parcel No*

Latitude 39. 29' 25.56 "N UTM E ☐ NAD 27
Longitude 119. 45' 44.93 "W UTM N x NAD 83/WGS 84

3. WORKED PERFORMED
x New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Monitor
x Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
x Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
top soil - hard pan			0	4
silty,soft silty clay toucn sand			4	7
silty clay touch of sand			7	10
blue packed silty clay			10	13
sand			13	16
light silty sand			16	17
sand			17	23
silty sand clay			23	25
silty sand			25	27
silty clay			27	30
silty sand			30	37
hard silty clay			37	40

Date started 26-Feb , 20 16
Date completed 26-Feb , 20 16

7. WATER QUALITIES
Static water level. 8 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
	NAD 27	
	39.490525	
	119.761463	

9. INSTRUCTION
Depth Drilled: 40 Feet Depth Cased: 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
24	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	SCH 40	0	40

ANNULAR MATERIALS
Sanitary Seal x Yes ☐ No

☐ Neat Cement	to		☐ Pumped	☐ Poured
☐ Cement Grout	to		☐ Pumped	☐ Poured
☐ Concrete Grout	to		☐ Pumped	☐ Poured
Bentonite Chips	6 to	8	☐ Pumped	x Poured
x Gravel Pack [> 0.2 in.]	0 to	40	☐ Pumped	x Poured
☐ Sand Pack [< 0.2 in.]	to		☐ Pumped	☐ Poured
☐ Other, explain:	to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: machine slot
Size of perforation: 0.032

From	Feet	To	Feet
20	Feet	40	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Viking Drillers, Inc *Contractor*
Address 5950 Granite Lake Drive, Granite Bay, CA 95746 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board* 0034680
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)* 2361
Signed: *Beginner performing actual drilling operations or contractor*
Date: 4/13/16

(Rev 12-13) **USE ADDITIONAL SHEETS IF NECESSARY** pg. of pg.