STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 125039
Permit No. 83333
Basin No. 137B

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73620
WELL NAME *(If applicable)*: DW77

1. OWNER/CLIENT NAME Round Mountain Gold Corp
MAILING ADDRESS PO Box 480
Round Mountain, NV 89045

DETAILED ADDRESS AT WELL LOCATION
Round Mountain Mine, Round Mountain NV
Subdivision Name *County.* Nye

2. PLS LOCATION NE ¼ SE ¼ 24 Sec 10 N N/S 43 E
PERMIT/WAIVER NO 83333/ORDER *Issued by Water Resources* 1233 *Current Parcel No*

Latitude UTM E 491755 ■ NAD 27
Longitude UTM N 4284219 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
■ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Monitor
■ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ■ Rotary ■ RVC
☐ Air ■ Mud ☐ Sonic
■ Other Flooded

6. LITHOLOGIC LOG

Material Encountered		Lost Circ.	Water Strata	From	To
Overburdern / Fill				0	40
Alluvial / Sands / Boulders				40	750
Clay				750	765
Sounder Pipe					
Blank	2.375	3.65	.154	+2	700
Slotted	2.375	3.65	.125	700	740

Date started: May 1st , 20 16
Date completed: May 26th , 20 16

7. WATER QUALITIES
Static water level: 548 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ■ Air Lift

G.P.M	Draw Down (Feet Below Static)	Recorded Time (Hours)
23	113	4
	NAD 27	
	38.708434	
	117.094827	

9. WELL CONSTRUCTION
Depth Drilled 765 Feet Depth Cased 760 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
26	inches	0	Feet	40	Feet
20	Inches	40	Feet	765	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	86.61	.375	0	40
12.750	49.56	.375	+2	760

ANNULAR MATERIALS
Sanitary Seal ■ Yes ☐ No

■ Neat Cement	0	to	58	■ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
■ Bentonite Chips	58	to	503	■ Pumped	☐ Poured
■ Gravel Pack [> 0.2 in.]	503	to	765	☐ Pumped	■ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation Full Flow Louvered
Size of perforation: 0.125

From	Feet	To	Feet
520	Feet	740	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.

Name Joshua Donison *Contractor*
Address 2745 W California Ave, Salt Lake City, UT 84104 *Contractor*
Phone (801) 973-6667
Nevada contractor's license number as issued by the *State Contractor's Board.* 21976
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)*: 2386
Signed: *By driller performing actual drilling on site or contractor*
Date. 6-14-16

(Rev. 04-16) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.