

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 125049  
Permit No. \_\_\_\_\_  
Basin No. 084

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73513  
WELL NAME (if applicable): \_\_\_\_\_

1. OWNER/CLIENT NAME Capurro Investments DETAILED ADDRESS AT WELL LOCATION 155 Paloma Ranch Ct.  
MAILING ADDRESS 955 Dayton Way Sparks NV 89434  
Subdivision Name: \_\_\_\_\_ County: Washoe

2. PLS LOCATION NW 1/4 SW 1/4 15 Sec 22 N/S 21 E Latitude 39.773198 UTM E  NAD 27  
PERMIT/WAIVER NO. 007-520-02 Longitude 119.619636 UTM N  NAD 83/WGS 84  
Issued by Water Resources Current Parcel No.

3. WORKED PERFORMED  
 New Well  Deepen: Orig WL# \_\_\_\_\_  
 Replacement: Original well log # \_\_\_\_\_  
 Recondition: Original well log # \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Monitor  Auger  Rotary  RVC  
 Mining / Dewater  Com / Ind  Stock  Air  Mud  Sonic  
 Test / Other  Mun / QM  Rec  Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Clay			0	5	5
Cobbles			5	38	33
Sand & Gravels			38	115	77
Clay			115	118	3
Sand & Gravels			118	225	107
Clay			225	236	11
Small to Large Gravels			236	448	212

9. WELL CONSTRUCTION  
Depth Drilled: 448 Feet Depth Cased: 448 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet
<u>11</u>	<u>0</u>	<u>448</u>	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6 5/8</u>		<u>1.188</u>	<u>43</u>	<u>448</u>

PERFORATIONS:

Type of perforation: Factory  
Size of perforation: 1/16

From	Feet	To	Feet
<u>428</u>		<u>448</u>	
<u>408</u>		<u>388</u>	
<u>368</u>		<u>348</u>	

ANNULAR MATERIALS

<input checked="" type="checkbox"/> Sanitary Seal	<u>0</u> to <u>54</u>	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Neat Cement	to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Cement Grout	to _____	<input type="checkbox"/> Pumped	<input checked="" type="checkbox"/> Poured
<input checked="" type="checkbox"/> Concrete Grout	<u>0</u> to <u>54</u>	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Bentonite Chips	to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Bentonite Grout	to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> 15% <input type="checkbox"/> 20% <input type="checkbox"/> Other, explain: _____			
<input checked="" type="checkbox"/> Gravel Pack [ > 0.2 in. ]	<u>54</u> to <u>448</u>	<input type="checkbox"/> Pumped	<input checked="" type="checkbox"/> Poured
<input type="checkbox"/> Sand Pack [ < 0.2 in. ]	to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Other, explain:	to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

7. WATER QUALITIES  
Date started: 5-20-16 , 20  
Date completed: 5-24-16 , 20

Static water level: 185 Feet below land surface  
Artesian Flow: 40 G.P.M. 40 P.S.I.  
Water Temperature: 66 ° Fahrenheit  
Water Quality: Cl/CO2

8. WELL TEST DATA

Test Method:	Bailer	Pump	Air Lift
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
G.P.M.	<u>40</u>	Draw Down (Feet Below Static)	Recorded Time (Hours)
<u>325'</u>		<u>NAD 27</u>	<u>3</u>
		<u>39.773295</u>	
		<u>119.618618</u>	

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision. This report is true to the best of my knowledge.  
Name: BLAIN DRILLING & PUMP CO INC.  
Address: Carson City, NV 89702  
Nevada contractor's license number as issued by the State Contractor's Board: 46998A  
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2321  
Signed: C. Robinson  
Date: 5-26-16