STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No 125228
Permit No
Basin No. 101

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 74634
WELL NAME (If applicable):

1. OWNER/CLIENT NAME Matthew Beebe
MAILING ADDRESS 4150 St. Clair Rd.
Fallon, NV 89406

DETAILED ADDRESS AT WELL LOCATION 4150 St. Clair Rd.
Fallon, NV 89406
Subdivision Name: County: Churchill

2. PLS LOCATION SW ¼ SE ¼ 4 Sec 18 N/S 28 E
PERMIT/WAIVER NO. 006-231-22
Issued by Water Resources Current Parcel No.

Latitude 39.44605 UTM E ☐ NAD 27
Longitude -118.84268 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☐ Deepen: Orig WL#
☒ Replacement: Original well log # Unknown
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Brown Sand			0	11
Brown Clay			11	15
Brown Sand			15	38
Brown Clay			38	40
Gray Sand			40	46
Black Sand			46	52
Gray Sand			52	74
Gray Clay			74	76
Brown Sand			76	82
Green Silt			82	104
Gray Clay			104	107
Gray Sand			107	125
Gray Clay			125	130
Gray Sand			130	142
Gray Clay			142	149
Brown Sand		X	149	160

Date started. 28-Jun , 20 16
Date completed. 29-Jun , 20 16

7. WATER QUALITIES
Static water level: 22 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
	NAD 27	
	39.446133	
	118.841693	

9. CONSTRUCTION
Depth Drilled: 160 Feet Depth Cased: 160 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12	Inches	0	Feet	160	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	0	20
6	4.1	SDR21	20	160

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☒ Neat Cement	0 to 100	☒ Pumped	☐ Poured
☐ Cement Grout	to	☐ Pumped	☐ Poured
☐ Concrete Grout	to	☐ Pumped	☐ Poured
☐ Bentonite Chips	to	☐ Pumped	☐ Poured
☒ Gravel Pack [> 0.2 in.]	100 to 160	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]	to	☐ Pumped	☐ Poured
☐ Other, explain:	to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Saw Cut
Size of perforation: 1/8.

From	Feet	To	Feet
157		160	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge
Name Parsons Drilling, Inc. (Contractor)
Address P.O. Box 1265 Fallon, NV 89407 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 29064
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 1753
Signed: (By driller performing actual drilling on site or contractor)
Date: 7/6/2016

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

Replacing unknown well log