STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 125233
Permit No. 83333
Basin No. 137B

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73610
WELL NAME (if applicable): DW-79

1. OWNER/CLIENT NAME Round Mountain Gold Corp.
MAILING ADDRESS PO Box 480, Round Mountain, NV. 89045

DETAILED ADDRESS AT WELL LOCATION Round Mountain Mine, Round Mountain, NV. 89045
Subdivision Name: County: Nye

2. PLS LOCATION SE ¼ NE ¼ 30 Sec 10 (N)S 44 E
PERMIT/WAIVER NO. 83333 (Issued by Water Resources) Order 1233 (Current Parcel No.)

Latitude UTM E 493362 [X] NAD 27
Longitude UTM N 4283165 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Deepen: Orig WL#
[ ] Replacement: Original well log #
[ ] Recondition: Original well log #

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Monitor
[X] Mining / Dewater [ ] Com / Ind [ ] Stock
[ ] Test / Other [ ] Mun / QM [ ] Rec

5. WELL TYPE
[ ] Auger [ ] Rotary [ ] RVC
[ ] Air [ ] Mud [ ] Sonic
[X] Other Flooded Rev

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Gray brown granite			0	530
Brown granite			530	650
Temporary well				
No gravel pack or annular seal				
Steel sealing ring welded between 8" and 12" casing.				

Date started: 7-May, 20 16
Date completed: 29-May, 20 16

7. WATER QUALITIES
Static water level: 86.3 Feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I.
Water Temperature: N/A ° Fahrenheit
Water Quality: Okay

8. WELL TEST DATA
Test Method: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
14	N/A	2

NAD 27
38.678949
117.076334

9. CONSTRUCTION
Depth Drilled: Feet 650 Depth Cased: 640 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
17.5	Inches	0	Feet	20	Feet
10.625	Inches	20	Feet	650	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12.75	49.56	.375	0	20
8.625	22.36	.250	+1.5	640

ANNULAR MATERIALS
Sanitary Seal X Yes [ ] No

[X] Neat Cement	0 to 20	[X] Pumped	[ ] Poured
[ ] Cement Grout	to	[ ] Pumped	[ ] Poured
[ ] Concrete Grout	to	[ ] Pumped	[ ] Poured
[ ] Bentonite Chips	to	[ ] Pumped	[ ] Poured
[ ] Gravel Pack [> 0.2 in.]	to	[ ] Pumped	[ ] Poured
[ ] Sand Pack [< 0.2 in.]	to	[ ] Pumped	[ ] Poured
[ ] Other, explain:	to	[ ] Pumped	[ ] Poured

PERFORATIONS:
Type of perforation: Louvered
Size of perforation: 0.125
From 40 Feet To 620 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Boart Longyear (Contractor)
Address 2745 California Ave., SLC., UT. 84104 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board. 0021976
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 1410
Signed: (By driller performing actual drilling on site or contractor)
Date: 30-May-16

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. 1 of pg. 1