

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 125337  
Permit No. \_\_\_\_\_  
Basin No. 049

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37981  
WELL NAME (if applicable): MW-11

1. OWNER/CLIENT NAME Bob Hardy / Hardy Enterprise Inc.  
MAILING ADDRESS PO Box 248  
Bountiful UT 84011

DETAILED ADDRESS AT WELL LOCATION 1790 Idaho St - Public Right A-way  
Elko NV  
Subdivision Name: \_\_\_\_\_ County: Elko

2. PLS LOCATION SE 1/4 SW 1/4 11 Sec 34 T16 S55 E  
PERMIT/WAIVER NO. M/O - 2063 001-560-001  
Issued by Water Resources Current Parcel No.

Latitude 40.842724 UTM E  NAD 27  
Longitude 115.751992 UTM N  NAD 83/WGS 84

3. WORKED PERFORMED  
 New Well  Deepen: Orig WL# \_\_\_\_\_  
 Replacement: Original well log # \_\_\_\_\_  
 Recondition: Original well log # \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Monitor  
 Mining / Dewater  Com / Ind  Stock  
 Test / Other  Mun / QM  Rec

5. WELL TYPE  
 Auger  Rotary  RVC  
 Air  Mud  Sonic  
 Other

6. LITHOLOGIC LOG				
Material Encountered	Lost Circ.	Water Strata	From	To
Silt, Moist Dark brown stiffy			0	
Clay w gravel moist, yellowish				10
Clay w gravel moist, yellowish brown			10	15
Clay W sand moist YB stiff clay			15	21
Clay w gravel moist, YB			21	26
Clay W Gravel moist YB stiff clay			26	34
Silty clay moist, YB verry stiff clay,				34
Clay W sand moist YB stiff clay			34	40
Clay W sand Wet YB			40	
Very stiff clay	<u>41</u>			51
Clay W gravel Wet, YB Verry stiff c			51	
Clay				64
Clay dry, pale YB 100% hard clay			64	65

9. INSTRUCTION  
Depth Drilled: 65 Feet Depth Cased: 65 Feet  
HOLE DIAMETER (BIT SIZE)  
From 0 To 65 Feet  
7.58 Inches \_\_\_\_\_ Feet  
\_\_\_\_\_ Inches \_\_\_\_\_ Feet  
\_\_\_\_\_ Inches \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2.375</u>	<u>0.68</u>	<u>0.154</u>	<u>0</u>	<u>64</u>

ANNULAR MATERIALS  
Sanitary Seal  Yes  No  
 Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout 0.5 to 9  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Bentonite Chips 9 to 12  Pumped  Poured  
 Gravel Pack [ > 0.2 in. ] \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Sand Pack [ < 0.2 in. ] 12 to 65  Pumped  Poured  
 Other, explain: \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Bentonite Chips - Poured from 135 to 76" Borehole

PERFORATIONS:  
Type of perforation: Factory  
Size of perforation: 0.02  
From 14 Feet To 64 Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet

Date started: 10-Jun , 20 16  
Date completed: 11-Jun , 20 16

7. WATER QUALITIES  
Static water level: 41 Feet below land surface  
Artesian Flow: NA G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: NA ° Fahrenheit  
Water Quality: NA

8. WELL TEST DATA

Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input checked="" type="checkbox"/> Bailor <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
		<u>NAD 27</u>	
		<u>40.842803</u>	
		<u>115.751091</u>	

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision. This report is true to the best of my knowledge.  
Name National EWP Contractor  
Address 4221 West Oquendo RD, Las Vegas, NV 89118 Contractor  
Nevada contractor's license number as issued by the State Contractor's Board 0678005 75355  
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): \_\_\_\_\_ 2512  
Signed: Bob Hardy  
Date: 6/21/2016  
By driller performing actual drilling on site or contractor