STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 125573
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37974
WELL NAME (If applicable): MW-10

1. OWNER/CLIENT NAME: Linda W. Peng Spring Mt. LV LLC
MAILING ADDRESS: PO Box 30580 Las Vegas, NV 89173

DETAILED ADDRESS AT WELL LOCATION: 3435 S. Jones Blvd
Las Vegas, NV
Subdivision Name: County: Clark

2. PLS LOCATION: NE ¼ NE ¼ 14 Sec 21 N/S 60 E
PERMIT/WAIVER NO.: MO-3166 (Issued by Water Resources) 163-14-502-010 (Current Parcel No.)

Latitude: 36.12634"N UTM E: ☑ NAD 27
Longitude: 115.22504"W UTM N: ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☑ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Asphalt			0	3"
Silty sand			3"	3
Caliche			3	4
Silty sand			4	14
Clayey sand			14	16
Silty sand			16	20
Sandy clay			20	25
Silty clay			25	28
Gravelly sand w/ silt			28	34
Clayey sand			34	37
Sandy clay			37	95
Silty sand			95	96

DCNR/DWR/SNBO
RECEIVED
MAY 19 2016

Date started: 2-May, 20 16
Date completed: 2-May, 20 16

9. CONSTRUCTION
Depth Drilled: 96 Feet Depth Cased: 96 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10.25	Inches	0	Feet	96	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	2.01	0.237	0	96

ANNULAR MATERIALS
Sanitary Seal ☑ Yes ☐ No

☐ Neat Cement		to		☐ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☑ Bentonite Chips	74	to	78	☐ Pumped	☑ Poured
☐ Gravel Pack [> 0.2 in.]		to		☐ Pumped	☐ Poured
☑ Sand Pack [< 0.2 in.]	78	to	96	☐ Pumped	☑ Poured
☑ Other, explain: Bentonite Slurry	1.5	to	74	☑ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Factory
Size of perforation: ..020

From	81	Feet	To	96 Feet
From		Feet	To	Feet
From		Feet	To	Feet
From		Feet	To	Feet
From		Feet	To	Feet

7. WATER QUALITIES
Static water level: Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name: National EWP (Contractor)
Address: 4221 W. Oquendo Rd. Las Vegas, NV 89118 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2526
Signed: (By driller performing actual drilling on site or contractor)
Date: 5/19/2016

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.