

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 125597  
Permit No. \_\_\_\_\_  
Basin No. \_\_\_\_\_

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37976  
WELL NAME (if applicable): MW-3

1. OWNER/CLIENT NAME Patrick Carson-Rebel Oil Co.  
MAILING ADDRESS 2200 S. Highland Dr.  
Las Vegas NV 89102

DETAILED ADDRESS AT WELL LOCATION 4665 E. Sunset Rd  
Henderson, NV  
Subdivision Name \_\_\_\_\_ County Clark

2. PLS LOCATION NW ¼ NE ¼ 5 Sec 22 N/S 62 E  
PERMIT/WAIVER NO. MO-3168 178-05-54-014  
Issued by Water Resources Current Parcel No

Latitude 36.070809 N UTM E  NAD 27  
Longitude -115.071494W UTM N  NAD 83/WGS 84

3. WORKED PERFORMED  
 New Well  Deepen: Orig WL# \_\_\_\_\_  
 Replacement: Original well log # \_\_\_\_\_  
 Recondition: Original well log # \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Monitor  
 Mining / Dewater  Com / Ind  Stock  
 Test / Other  Mun / QM  Rec

5. WELL TYPE  
 Auger  Rotary  RVC  
 Air  Mud  Sonic  
 Other

Material Encountered	Lost Circ.	Water Strata	From	To
Asphalt			0	2"
Type 2 Base			2"	6"
Light brown well gradrd sand w/ little gravel			6"	6'
yelowish brown sand w/gravel caliche deposits			6'	15'
yellowish gray well grained sand w/little gravel			15'	20'
dark yellowish brown well graind sand some gravel caliche deposits			20'	25'
light brn sandy silt w/trace gravel			25'	30'
poorly cemented w/caliche			30'	32'
pale yellowish brn sandy silt Caliche			32'	33'
pale yellowish brn sandy silt w/ little gravel			33'	50'

9. INSTRUCTION  
Depth Drilled: 50' Feet Depth Cased: 45' Feet

HOLE DIAMETER (BIT SIZE)			
From	To	From	To
<u>8.25</u> Inches	<u>0</u> Feet	<u>50'</u> Feet	

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2.375</u>	<u>0.68</u>	<u>0.154</u>	<u>0</u>	<u>45</u>

ANNULAR MATERIALS  
Sanitary Seal  Yes  No  
 Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout 1 to 25  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Bentonite Chips 25 to 27  Pumped  Poured  
 Gravel Pack [ > 0.2 in. ] \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Sand Pack [ < 0.2 in. ] 27 to 45  Pumped  Poured  
 Other, explain: 46' to 50'  Pumped  Poured  
Bentonite Chips

PERFORATIONS:  
Type of perforation: Factory  
Size of perforation: 0.02  
From 30 Feet To 45 Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet

Date started: 11-May , 20 16  
Date completed: 11-May , 20 16

7. WATER QUALITIES  
Static water level: 35' Feet below land surface  
Artesian Flow: NA G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: NA ° Fahrenheit  
Water Quality: Clear

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision. This report is true to the best of my knowledge.  
Name National EWP Contractor  
Address 4221 West Oquendo Rd Las Vegas, NV 89118 Contractor

8. WELL TEST DATA			
Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input checked="" type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

Nevada contractor's license number as issued by the State Contractor's Board 0075355  
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2512-LTD  
Signed: Bob [Signature]  
By driller performing actual drilling on-site or contractor  
Date: 6/7/2016

NAD27 36.0708347  
-115.070665