STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 125619
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO 37941
WELL NAME *(If applicable)*: IW-3

1. OWNER/CLIENT NAME: GB Nevada Real Estate LLC
MAILING ADDRESS: 3159 W. Buckeye Rd.
Pheonix AZ 85009-5636

DETAILED ADDRESS AT WELL LOCATION: 3873 S. Las Vegas Blvd
Las Vegas, NV
Subdivision Name:
County: Clark

2. PLS LOCATION: SW ¼ NW ¼ 28 Sec 21 N(S) 61 E
PERMIT/WAIVER NO.: MO-3143 *Issued by Water Resources* 162-28-201-001 *Current Parcel No.*

Latitude: 36* 05' 49.57" N
Longitude: 115* 10' 19.93" W
UTM E:
UTM N:
☑ NAD 27
☐ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☑ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Asphalt			0	3"
Silty sand with gravels			3"	5'
yellowish-orange, fine sand				
, trace coarse-fine subangular				
gravel trace medium				
coarse sand				
sand with silt			10'	
and gravel, yellowish-orange				
fine sand, fine				
subangular gravel				18'
Caliche			18'	23'
Sandt silt with fine gravel fine			23'	
snad,fine subangular gravel, light				
grey, slight plasticity				27
Caliche			27'	34'

DCNR/DWR/SNBO
RECEIVED
MAR 21 2016

Date started: 16-Feb , 20 16
Date completed: 16-Feb , 20 16

9. CONSTRUCTION
Depth Drilled: 34 Feet Depth Cased: 34 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8.25	Inches	0	Feet	34	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.984	0.218	0	34

ANNULAR MATERIALS
Sanitary Seal ☑ Yes ☐ No

☐ Neat Cement		to		☐ Pumped	☐ Poured
☑ Cement Grout	5	to	17	☑ Pumped	☐ Poured
☑ Concrete Grout	5	to	1	☐ Pumped	☑ Poured
☑ Bentonite Chips	17	to	22	☐ Pumped	☑ Poured
☐ Gravel Pack [> 0.2 in.]		to		☐ Pumped	☐ Poured
☑ Sand Pack [< 0.2 in.]	23	to	34	☐ Pumped	☑ Poured
☑ Other, explain:	22	to	23	☐ Pumped	☑ Poured

Sanitary Seal 0/30 sand

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02

From	Feet	To	Feet
24	Feet	34	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

7. WATER QUALITIES
Static water level: NA Feet below land surface
Artesian Flow: NA G.P.M. P.S.I.
Water Temperature: NA ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name: National EWP (Contractor)
Address: 5241 Schirlls St. Las Vegas, NV 89118 (Contractor)
Nevada contractor's license number as issued by the *State Contractor's Board*: 0075355
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)*: 2512-LTD
Signed: Bal
By driller performing actual drilling on site or contractor
Date: 3/17/2016

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

36.097102
-115.1722
NAD 27