

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
 WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
 Log No. 125699
 Permit No. 13762
 Basin

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 39006

1 OWNER William DeWitt
 MAILING ADDRESS Po Box 1521
Southgate, Cal. 90380
 LOCATION NE 1/4 SE 1/4 Sec 14 T 16 N R 48 E
 PERMIT/WAIVER No. 15702 1019-031-12
Issued by Water Resources Parcel No.

ADDRESS AT WELL LOCATION 751 N. Cascade Way
Amargosa Valley, Nv.
 Subdivision Name: County: Nye
 Latitude 36.56147° UTM E NAD 27
 Longitude 116.52557° N NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? YES
 If yes, what is replacement well NOI? 39005
 Is there an existing well log? YES
 If yes, what is NDWR well log #? 4379

4 EXISTING WELL CONSTRUCTION

Depth Drilled 240 Feet Depth Cased 240 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>12</u>		<u>.250</u>	<u>0</u>	<u>240</u>

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why: Broken casing

Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no

Existing Perforations:
 Type of perforation Mills knife
 Size of perforation 3/4 x 2

From <u>7.5</u>	feet to <u>12.5</u>	feet
From	feet to	feet

If casing was left in place, please show where additional perforations were made:
 Additional Perforations:
 Type of perforator used: Mills knife

From <u>7.5</u>	feet to <u>12.5</u>	feet	Number of perfs per linear foot <u>4</u>
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL

Static water level 126.0 feet below land surface
 Artesian flow G.P.M. P.S.I.
 Water temperature °F Quality

8 WELL PLUGGING MATERIALS

Material Used			
From <u>0</u>	feet to <u>127</u>	feet	<u>Cement</u> <input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
Well had broken casing @ 127' perforated up to 7.5' and pumped full of cement.

Neat Cement Fluid Weight 15.6 lbs/gal
 Bentonite Grout % bentonite
 Date Started June 23, 2016
 Date Completed June 24, 2016

DCNR/DWR/SNBO
 RECEIVED
 JUL 22 2016

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Nv. Webber Drilling Contractor
 Address Po Box 40 Overton, Nv. 89040 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0025887
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2238

Signed Bryan Anzalone
By driller performing actual drilling on-site or contractor
 Date July 15, 2016

USE ADDITIONAL SHEETS IF NECESSARY

NAD 27 36.5615174
 -116.524686