

WELL DRILLERS REPORT

Please complete this form in its entirety

1. OWNER JAN SCHADE ADDRESS 1936 ZEPHYR WAY
 SPARKS, NEVADA 89431

2. LOCATION 1/4 1/4 Sec. 24 T. 21 N/S R. 18 E. WASHOE County
 PERMIT NO. SILVER KNOLLE 10235 SHANANDOAH

3. TYPE OF WORK
 New Well Recondition
 Deepen Other
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal Industrial Stock
 5. TYPE WELL
 Cable Rotary
 Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
SANDY OVER BURDEN		0	4	4
DRY LIGHT BROWN CLAY		4	28	24
sticky BROWN CLAY WITH DECOMPOSED GRANTIE		28	91	63
SOFT DECOMPOSED GRANITE & SAND		91	104	13
BROWN CLAY (SANDY) WITH SAND STRINGERS		104	175	71
WATER BEARING FRACTURES FOUND AT: 91', 120', 146'.				

8. WELL CONSTRUCTION
 Diameter hole 6 inches Total depth 178 feet
 Casing record 176' of 6-5/8 OD .188
 Weight per foot Thickness 188

Diameter	From	To
6-5/8 inches	0	176
inches		

 Surface seal: Yes No Type CEMENT
 Depth of seal 50 feet
 Gravel packed: Yes No
 Gravel packed from 50 feet to 188 feet
 Perforations:
 Type perforation FACTORY SAWED SLOTS
 Size perforation 3/32" X 2 1/2 X 6 Around
 From 141 feet to 161 feet
 From 80 feet to 100 feet
 From feet to feet
 From feet to feet

9. WATER LEVEL
 Static water level 81 Feet below land surface
 Flow 16 G.P.M.
 Water temperature ° F. Quality

Date started 11-16, 1977
 Date completed 11-16, 1977

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

10. DRILLERS CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC.
 Address P.O. BOX 347 NEWCASTLE CA.
 Nevada contractor's license number 14043
 Nevada driller's license number 471
 Signed Wayne Redman
 Date 11-21-77

BAILER TEST
 G.P.M. Draw down feet hours
 G.P.M. Draw down feet hours
 G.P.M. Draw down feet hours