

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 19645  
 Rec. 19  
 Well No. ....  
 Permit No. 38285  
*Do not fill in*



Owner Susie B. Smith (Cass's Trailer Ct.) Driller S.R. McKinney & Sons, Inc.

Address Indian Springs, Nevada Address 1042 So. Main Lic. No. 45

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. ...., T. 16 N/S, R. 56 E, in Clark Parcel # 059-08-000 <sup>610-126</sup> County Clark  
 or Indian Springs, Nevada

Water will be used for Domestic Use Total depth of well 100'

Size of drilled hole 12" to 50', 10" to 100' Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water .....

Diameter and length of casing 8" ID from 0' to 100'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 31'

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well 5/3/62 Date of completion of well 6/5/62

Type of well rig Bucyrus Erie 24L

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	clay & gravel
8	28	20	clay & gravel
28	34	6	gravel
34	45	11	gravelly clay
45	50	5	cement gravel (water)
50	65	15	cemented gravel
65	74	9	cement gravel (water)
74	77	3	brown clay
77	85	8	cement gravel
85	90	5	gravelly clay
90	100	10	cement gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 90 to 100 ft.

Other aquifers 45 to 50'  
65 to 74'

First water at 45 feet.

Casing perforated  
 from 55' to 100' ft.

Size of perforations  
3/16" X 10"

