WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLERS REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 23428
Permit No. 41989
Basin

1. OWNER U.S. Gov. Air Force ADDRESS MX Ballistic Missle Office
by Fugro Inc. 3777 Long Beach Blvd. Long Beach, California

2. LOCATION N.W. ¼ N.E. ¼ Sec. 12 T. 12 N. N/S R. 63 E. MDB &M -White Pine County
PERMIT NO 41989-W-047 in Southern Steptoe Valley

3. TYPE OF WORK
New Well ☐ Recondition ☒
Deepen ☐ Other ☒

4. PROPOSED USE
Domestic ☐ Irrigation ☐ Test ☒
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
See Attached Lithologic Log Form J.H. Kleinfelder & Associates				
This Hole has been cemented from the bottom up to leave a depth of 948 which is 10 ft. up into the bottom of the casing				
Tests were not completed on this well until Jan 1981.				
While drilling, water was found at 504 ft and at 708 ft. This was cased and cemented offtin order to drill deeper. After the hole was drilled to 2447 ft. it was later perforated and then pumped but the water has apparently been partly shut off by the cement				

Date started September, 1980
Date completed January, 1981

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pumping
(427-550)	100	123 ft.	2 Hrs.
(4270605)	125	178 ft.	2 Hrs.

pump intake was set at 605 ft.
Test made by Rhodes Pros. out of Fillmore, Utah

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter hole 5-7/8 inches Total depth 2447 feet
Casing record 0-50 ft. 8" 0-958 ft. 6"
Weight per foot ..... Thickness .....

Diameter		From	To
9 7/8" Hol	inches	feet	feet
8"	inches casing	0 feet	50 feet
7 7/8"	inches	feet	feet
6"	inches Casing	0 feet	958 feet
	inches	feet	feet
	inches	feet	feet

Surface seal: Yes ☐ No ☒ Type cement Groot
Depth of seal 50 ft. feet
Gravel packed: Yes ☐ No ☒
Gravel packed from ..... feet to ..... feet

Perforations:
Type perforation Machine
Size perforation 1/2" spaced 120° every 3"
From 500 feet to 543 feet
From 743 feet to 940 feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet

9. WATER LEVEL
Static water level 427 Feet below land surface
Flow [redacted] G.P.M. 100 to 0
Water temperature °C. °F. Quality good

10. DRILLERS CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Walter Rodney Miller
Address P.O. Box 818 Fallon, Nevada
Nevada contractor's license number 005380
Nevada driller's license number 961
Signed Walter Rodney Miller
Date January 31, 1981

USE ADDITIONAL SHEETS IF NECESSARY

O-627