

OFFICE USE ONLY
 Log No. 31461
 Permit No. _____
 Basin 6-25

WELL DRILLER'S REPORT

Please complete this form in its entirety

NOTICE OF INTENT NO. 9224

PRINT OR TYPE ONLY

1. OWNER DANNY DEGNER ADDRESS AT WELL LOCATION Same
 MAILING ADDRESS 5050 Dolores Sparks, NV 89436

2. LOCATION NW 1/4 SW 1/4 Sec 4 T 20N N/S R 20 E Washoe County
 PERMIT NO. 83-440-54 Spanish Springs
Issued by Water Resources Parcel No. Subdivision Name

3. TYPE OF WORK
 New Well Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal Industrial Stock

5. TYPE WELL
 Cable Rotary
 Other Air

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sandy clay		0	2	2
Sandy brown clay with soft streaks		2	22	20
Brown clay tight		22	116	94
Soft zone		116	119	3
Brown sandy clay		119	131	12
Soft zone		131	136	5
Brown sandy clay		136	152	16
Soft zone	X	152	161	9
Brown clay tight		161	169	8
Soft zone		169	173	4
Brown clay tight		173	180	7
Gray sandy clay harder		180	206	26
Black clay softer		206	221	15
Chocklate brown clay softer		221	225	4
Tan clay softer		225	236	11
harder		236	250	14
Sand streak	X	250	253	3
Gray granite		253	287	34
with Fracture at	X	274		
Light gray weathered rock		287	293	6
Dark gray weathered rock		293	312	19
Clay streaks, gray		312	320	8
Broken & fracture rock	X	320	340	20

8. WELL CONSTRUCTION
 Diameter 6 inches Total depth 340 feet
5 inches
340' steel casing installed.
 Casing record _____ Thickness .156
 Weight per foot _____

Diameter	From	To
<u>6 5/8</u> inches	<u>0</u> feet	<u>280</u> feet
<u>5</u> inches	<u>260</u> feet	<u>340</u> feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet

Surface seal: Yes No Type cement
 Depth of seal 50 feet
 Gravel packed: Yes No
 Gravel packed from 50 feet to 340 feet

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 6 around
 From 230 feet to 270 feet
 From _____ feet to _____ feet

Date started 4-10-89
 Date completed 4-14-89

9. WATER LEVEL
 Static water level 120 feet below land surface
 Flow 18 G.P.M. P.S.I.
 Water temperature cold °F Quality clear

7. WELL TEST 68.8

Pump RPM	G.P.M.	Draw Down	After Hours Pump

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling, Inc.
 Contractor
 Address P.O. Box 12370, Reno, NV 89510
 Contractor
 Nevada contractor's license number 22549
 issued by the State Contractor's Board
 Nevada contractor's driller's number 908
 issued by the Division of Water Resources
 Nevada driller's license number issued by the 908
 Division of Water Resources, the on-site driller
 Signed Wayne C. Adams
 By driller performing actual drilling on site or contractor
 Date April 29, 1989

BAILER TEST

G.P.M.	Draw down	feet	hours