WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 51906
Permit No.
Basin 087

NOTICE OF INTENT NO. 30626

1. OWNER DR. MERLE F. & JOY BRUCE
MAILING ADDRESS 100 Sawbuck Rd.
Reno, Nevada 89509

ADDRESS AT WELL LOCATION
125 Anitra Dr.
Reno, Nevada 89511

2. LOCATION NE ¼ SW ¼ Sec. 2 T. 18N N/S R. 19E E. Washoe County
PERMIT NO. R-290 (Issued by Water Resources) 041-290-23 (Parcel No.) Anitra Subdivision (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown clay & boulders		0	2	2
Gray Volcanic rock		2	12	10
Yellow " "		12	17	5
Rusty brown " "		17	21	4
Yellow clay		21	66	45
Yellow volcanic rock		66	79	13
Brown " "		79	114	35
Yellow " "		114	133	19
Brown " "		133	179	46
Fracture rock	X	179	189	10
Brown volcanic rock		189	190	1
Gray " "		190	210	20
Fracture	X	210	215	5
Gray volcanic rock		215	279	64
Fracture rock	X	279	287	8
Gray volcanic rock		287	300	13

Date started 4-23-96, 19
Date completed 4-24-96, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50+		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	300 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation Factory sawed slot
Size perforation 3/32 x 3 x 5 around
From feet to feet
From 195 feet to 215 feet
From 275 feet to 295 feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 138 feet below land surface
Artesian flow G.P.M. 50+ P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed (By driller performing actual drilling on site or contractor)
Date April 26, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627

Replaced by Well Log 123709