WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 32046
Permit No. 48999
Basin 04-072 Imlay Area

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 12098

1. OWNER Pegasus
MAILING ADDRESS P.O. Box 330
Imlay, NV 89418

ADDRESS AT WELL LOCATION Florida Canyon Mine

2. LOCATION SW ¼ NW ¼ Sec. 3 T. 31 N/S R. 33 E. Pershing County

PERMIT NO. 48999 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE Mining
Domestic ☐ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Boulders w/s sand & trace of clay		0	8	8
Boulders w/s sand & 50% clay		8	10	2
Boulders w/s sand & 25% clay		10	55	45
Cobbles w/s gravel & 30% clay		55	260	205
Brown sandy clay		260	315	55
Cobbles w/s gravel & 30% clay		315	325	10
95% red sandy clay w/s cobbles		325	405	80
95% gray sandy clay w/s cobbles		405	420	15
Sand & gravel w/s cobbles & 20% clay		420	445	25
Sand & gravel w/s 40% clay		445	664	219
Fractured riolite w/s trace of clay		664	683	19
No return		683	690	7
Fractured riolite		690	695	5
No return		695	716	21
Fractured riolite		716	730	14

Date started 7/10, 19 89
Date completed 7/31, 19 89

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	600	450'	3

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter 16 inches Total depth 730 feet
..... inches
..... inches
Casing record 10"
Weight per foot ..... Thickness ¼

Diameter	From	To
10" SS Blank inches	0 feet	410 feet
10" SS Lvrd inches	410 feet	670 feet
10" SS Screen inches	670 feet	730 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type Concrete
Depth of seal 50 feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 50 feet to 730 feet

Perforations:
Type perforation Louverd .070 Screen .080
Size perforation 10" Stainless Steel
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet
From ..... feet to ..... feet

9. WATER LEVEL
Static water level 125 feet below land surface
Flow ..... G.P.M. ..... P.S.I.
Water temperature 192 °F Quality .....

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 592 Winnemucca, NV 89445 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada contractor's driller's number issued by the Division of Water Resources C-23
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1448
Signed [signature] By driller performing actual drilling on site or contractor
Date 8/03/89

RECEIVED
STATE ENGINEERS OFFICE
89 AUG -8 AM 10:14

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O)-627