CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

DIVISION OF WATER RESOURCES

WELL DRILLERS REPORT

Please complete this form in its entirety

Log No. 35273
Permit N
Basin 8-101

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 12[illegible]

1. OWNER Roy Huckins
MAILING ADDRESS 11355 Reno Highway
ADDRESS AT WELL LOCATION 11355 Reno Highway

2. LOCATION SW ¼ NE ¼ Sec. 17 T. 19 N/S R. 27 E Churchill County
PERMIT NO. 51964 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. TYPE OF WORK: New Well ☑ Recondition ☐ Deepen ☐ Other ☐

4. PROPOSED USE: Domestic ☐ Irrigation ☑ Test ☐ Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL: Cable ☐ Rotary ☑ Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	6'	6
Sand		2	60'	54
Clay		60	65	5
Clay & Fine gravel		65	70	5
" & Coarse Sand	—	70	80	10
Clean Coarse Sand	—	80	110	30
Squeezing Clay	—	110	112	2
Clay & Coarse Sand		112	130	18
Sticky Gay Clay	—	130	150	20
Rock or Boulders		150	153	3
Rock & Green Clay	Hard	153	158	5
Cement Sand	Hard	158	162	4
Conglomerate Rock	Hard	162	175	13
Gray Clay & Sand		175	180	5
Volcanics	Hard	180	185	5
Coarse Sand Some	Clay	185	200	15
Small gravel Sharp	Rock	200	205	5
Small gravel mult.		205	275	70
Colored easy drilling				
Tan Clay mixed with		275	285	
blue Stringers		285	T.D.	

Date started Oct. 11, 1989
Date completed Nov. 7, 1989

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
Air Lifted	App.		500 g.p.m.

BAILER TEST

G.P.M. — Draw down — feet — hours
G.P.M. — Draw down — feet — hours
G.P.M. — Draw down — feet — hours

8. WELL CONSTRUCTION

Diameter hole 18 inches Total depth 285 feet
Casing record
Weight per foot Thickness .188

Diameter	From	To
12 inches	-2 feet	285 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☑ No ☐ Type Concrete
Depth of seal 8' X 8' X 8' feet
Gravel packed: Yes ☑ No ☐
Gravel packed from 285 feet to 50 feet

Perforations:
Type perforation Saw Cut
Size perforation
From ~~283~~ 270 8 feet to ~~[illegible]~~ 210 feet
From 120 feet to 100 feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL

Static water level 43 feet below land surface
Flow — G.P.M. — P.S.I.
Water temperature ° F. Quality good

10. DRILLERS CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Potter Drilling Co (Contractor)
Address P.O. Box 1515 Fallon (Contractor)
Nevada contractor's license number 201618
Nevada contractor's drillers number
Nevada driller's license number 1348 (Actual Driller)
Signed [signature] (Contractor)
Date 11-13-1989

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 6-81) O-627 CR434